

SAFETY – PERFORMANCE - ECONOMY

KEEP THAT MOTOR RUNNING!

Fortified with Prolong's advanced lubrication technology, nothing works better than Prolong Oil Stabilizer! Formulated to help maximize protection and performance, and help solve the following lubrication problems:

- **STOPS OIL LEAKS** – Conditions seals to help stop oil leaks
- **REDUCES OIL BURNING** – Seals worn cylinders and valve guides to slow oil consumption
- **REDUCES ENGINE NOISE** - Adds lubricity to motor oil to help quiet engine knocking
- **REDUCE EXHAUST SMOKE** – Slows blow-by to help reduce smoke and emissions
- **INCREASES COMPRESSION** – Seals around piston rings to help restore compression.
- **REDUCES FRICTION & HEAT** – Extreme pressure technology to reduce friction so that engines run cooler
- **EXTENDS OIL LIFE** – Antioxidants help slow oil breakdown to keep oil cleaner, longer
- **STABILIZES VISCOSITY** – Helps maintain oil viscosity in hot or cold weather
- **COLD START PROTECTION** – Special additives and Prolong's AFMT+ helps provide engine protection



USE WITH CONFIDENCE

- Non-corrosive antioxidant formula
- Will not void engine warranties
- Effective for both gas and diesel engines
- Compatible with petroleum or synthetic oils
- Helps prevent sludge and varnish deposits

Directions

- **Regular Gasoline Engines**, use 20% (1 qt. Oil Stabilizer with 4 qts. of oil) For badly worn engines, use 40% (2 qts. Oil Stabilizer with 3 qts. oil)
- **Diesel Engines**, use 20% by volume (Commercial, Industrial, Farm and Fleet, Marine.)
- **Manual Transmissions Only, Differentials and Gear Boxes**, use 20% by volume.
- **Motorcycles, Air Compressors, Lawn Mowers, etc.**, use 20% by volume.

OUTPERFORMS OTHER PRODUCTS:

	OTHER OIL STABILIZERS	PROLONG SUPER HEAVY DUTY STABILIZER
TACKINESS AGENT	✓	✓
VISCOSITY MODIFIER	✓	✓
ANTI-WEAR AGENT		✓
ANTIOXIDANT		✓
EXTREME PRESSURE AGENT		✓
LUBRICITY STABILIZER		✓
ANTI-SCUFF AGENT		✓
DETERGENT INHIBITOR		✓
SEAL CONDITIONER		✓
METAL TREATMENT		✓

Product Packaging:

Part Number	Size	Case Qty
13032	1 quart (32 oz)	6
13128	1 gallon (3.78 L)	4

Distributed By:

GoldenWest Lubricants, Inc.
 1937 Mount Vernon Avenue
 Pomona, CA 91768
 Phone: 800.540.LUBE(5823)