

FLEX CLEAN

NO CAUSTICS - NO VOCs - NO LISTED MATERIALS

Formulated with multiple detergents, cleaners and Anti re-deposition agents dissolve, lift and remove without allowing any contaminates to be re-deposit on areas being cleaned.

A strong and more eco friendly cleaner, for today's environments. Removes ingrained ink, coatings, pigments, residues and other contaminates, away from anilox roller cells, plates and press parts. Low foaming formula.

- FLEX CLEAN can be cut with 25% up to 50% water.
- General aqueous and UV ink flexo wash.
- Removes coatings and varnishes from a variety of surfaces.
- General purpose shop cleaner: Cement floors, rugs, rubber mats, press frames and parts.
- Use as a manual or auto wash for/in (Anilox-Plate Ultrasonic-Parts).
- Non-Flammable
- Not regulated for shipping

Direction For Use:

Anilox Manual Wash:

Apply onto anilox roller using a brush or shop towel to scrub and remove ink pigments, coatings and residues.

Parts Manual Wash:

Spray or immerse part(s) 1-30 minutes. Remove parts from the cleaner. Quickly, use a plastic or brass brush to gently scrub stubborn contaminants loose. Rinse the parts in water, let air dry, or dry with a shop towel.

Specifications:

VOC content lb. / gallon	None
VOC content grams / liter	None
Flashpoint	None
Color	Clear
CA. Compliant	Yes



Ultrasonic Bath/Soak Tank:

Utilizing existing time/cycle settings: Apply full strength or dilute 1:4 parts water to determine cleaning strength and results desired.

Floors & Walls:

Spray surface directly or dilute with water to determine desired cleaning strength. Clean area with mop, brush or squeegee. Final rinse with water.

Available In:

Product Code	Unit	Case Qty.
81015D	1 Gallon (3.785 ltr)	4
81015E	5 Gallons (18.9 ltr)	Each
81015G	55 Gallons (208 ltr)	Each
81015T	275 Gallons (1040 ltr)	Each

