

ANCHOR PRIME SPRAY PAINT



PAINTS OF DISTINCTION



Description

Anchor Prime is an advanced range of primers that ensures superior adhesion of paint to the surface, increases paint durability and provides additional corrosion protection. Anchor prime has a large range of specialised primers suitable for metal, timber and plastic.

Specification

Propellant, a blend of Hydrocarbons & Dimethyl Ether.

Directions

Ideal temperature 16°C - 25°C. Degrease metals and grind them smoothly. Ensure the surface is clean & free from dust. Shake the can vigorously for at least one minute after hearing clearly the audible striking of the metal ball. Apply the spray crosswise from a distance of approx. 25-30cm. The surface is dry after 5-7 minutes depending on the temperature. Allow 10 minutes between coats. 2 - 3 coats are desirable. Can be over coated with a suitable anchor top coat after 30 minutes.

Surface Preparation

Ensure the surface is clean & free from dust. A quality wax & grease remover can be used.

Packaging

300 gram aerosol can
12 units per carton
1152 units per pallet

ANCHOR PRIME SPRAY PAINT



Storage/Shelf Life

Store in a cool place out of the sun. Do not store above 50°C

Health & Safety

Aerosols should be completely empty before disposing. Recycle empty can if facility is available. Ensure adequate ventilation when using in enclosed areas. Keep away from heat, flames or sources of ignition.

Limitations

Avoid applying at temperatures below 10°C or in damp conditions. When applying at temperatures above 30°C, do a test spray to ensure the desired finish is achieved.

Disclaimer

CW Brands Pty Ltd believes that the information in this technical data sheet is an accurate description of the typical uses of the product. The data and statements are based on our research and development work and is to the best of our knowledge true and accurate. The user must ensure of the product(s) in their application prior to use in particular to determine its performance, efficiency and safety. The use of this product is beyond the manufacturer's control, and liability is restricted to the replacement of material proven faulty. The manufacturer is not responsible for any loss or damage arising from incorrect usage. Products conform solely to the information contained in this and other related CW Brands Pty Ltd publications. CW Brands Pty Ltd reserves the right to make changes to specifications and information related to the products at any time. Users are asked to check that the literature in their possession is the latest issue. Statements contained herein should not be considered as a warranty of any kind, expressed or implied in describing the performance or suitability of the product for a particular application. No liability is accepted for infringement of any patents or any other intellectual property right.