



VC Liquid CARTRIDGE HOUSINGS

VC Liquid Cartridge Housings offer the versatility of choosing the correct multiple cartridges to meet flow rate, chemical compatibility and particle retention requirements. VC housings accommodate from one to seven elements in 10-, 20-, 30- and 40-inch lengths, depending on the model. Includes band clamp closure.

APPLICATIONS

- Commercial
- General Industrial

VC LIQUID Cartridge Housings

ORDERING INFORMATION

		Cartridge Length				Connection Size
		10"	20"	30"	40"	
Number of Cartridges	1	VC1101NB4D10	VC1201NB4D10	VC1301NB4D10	—	1" NPT
	—	—	—	—	—	—
	—	—	—	—	—	—
Part Number						

FEATURES

- Flow rates up to 120 gpm
- 304 Stainless Steel material, polished finish
- Each vessel is factory hydro-tested
- Accepts 10-, 20-, 30- and 40-inch cartridge lengths (quantity per housing varies)
- Accepts double open ended cartridges
- Quick swing strap band closure
- EPDM lid seal
- Vent ports
- 100 PSI Pressure rating
- Buna or Viton O-Rings available separately

DIMENSIONS

Part No.	E	F	G
VC1101NA4D10	14.06" (357 mm)	4.33" (110 mm)	3.5" (89 mm)
VC1201NA4D10	24.02" (610 mm)	4.33" (110 mm)	3.5" (89 mm)
VC1301NA4D10	33.39" (848 mm)	4.33" (110 mm)	3.5" (89 mm)

