



VB88

Single Liquid BAG HOUSINGS

VB88 Single Liquid Bag Housings effectively remove dirt, pipe scale, and other contaminants from process liquids. Quality construction and design assure protection for all downstream equipment. Includes band clamp closure.

APPLICATIONS

- Chemical
- General Industrial
- Oil and Gas
- Water

HOUSING OPERATION

Unfiltered liquid enters the housing above the filter bag, filling the interior of the housing and continuing through the bag. Solids are trapped inside the filter bag and are easily removed when the housing is serviced.

FEATURES

- Flow rates up to 120 gpm
- Accepts #2-size bag filters
- 304 Stainless Steel material, polished finish
- Factory hydro-tested
- Quick strap band closure
- Strainer baskets included
- EPDM seals, lid and basket
- Vent ports
- Bag hold down device
- Buna or Viton O-Rings available separately

SPECIFICATIONS

Pressure Rating	100 PSI at 300°F (300°F requires Viton O-rings, sold separately)
Connections	2-inch NPT
Housing Lid	Quick strap band closure
Lid Seal	EPDM
Inlets/Outlets	Side inlet/Bottom outlet
Construction/Finish	Stainless Steel w/polished finish
Bags Sizes	#2 liquid bags accepted
Base	Adjustable tripod leg assembly standard



**Pentair
Industrial**

VB88 SINGLE LIQUID Bag Housings

ORDERING INFORMATION

Part Number	Bag Size	Connection Size
VB88302NA410	#2	2" NPT

DIMENSIONS

