

PENTEK® ST-BC STAINLESS STEEL SERIES FILTER HOUSINGS

THE SHAPE OF THE THE SHAPE OF THE THE SHAPE OF THE THE SHAPE OF THE SH

Telefone: 41 3081-3050

IDEAL FOR HIGH-TEMPERATURE APPLICATIONS REQUIRED FOR HEAVY DUTY FILTRATION NEEDS



Pentair® Pentek® ST-BC Series Stainless Steel Filter Housings offer a variety of solutions for your large-scale, heavy duty filtration needs. Simple to install and maintain, these housings are ideal for schools, restaurants, farms, institutions and industrial use. Holding from 4 to 20 cartridges, ST-BC Series Housings provide flow rates from 28-125 gpm (106-473 Lpm).

Housings are constructed of 304 stainless steel with a gray-silver epoxy finish. They include drains on both the "clean" and "dirty" sides of the sump.

ST-BC Series Housings are compatible with a complete range of filter cartridges, adding to their versatility.

FEATURES/BENEFITS

Heavy duty units for large scale commercial/industrial applications

Brushed 304 stainless steel construction with a gray-silver epoxy finish

Ideal for high-temperature applications

Accepts complete range of standard double open end (DOE) cartridges

SPECIFICATIONS

Housing – Brushed 304 stainless steel

Exterior finish – Epoxy

Temperature Rating-40-300°F (4.4-149°C)

Maximum Pressure – 125 psi (8.6 bar) Pipe Size – 2" NPT

Sealing Gasket – Buna-N®

SPECIFICATIONS AND PERFORMANCE

PART	DESCRIPTION	RECOMMENDED* FLOW RATES	DIMENSIONS HEIGHT X O.A. DIA	MAX. CARTRIDGE DIAMETER	MAXIMUM CARTRIDGES LENGTH
156025-02	ST-BC-4 (Holds 4-10" Cartridges)**	28 gpm (106 Lpm)	19.25" x 10" (489 mm x 254 mm)	3" (76 mm)	9.75" or 10" (248 mm or 254 mm)
156026-02	ST-BC-8 (Holds 8-10" or 4-20" Cartridges)**	56 gpm (212 Lpm)	29" x 10" (737 mm x 254 mm)	3" (76 mm)	9.75" or 10" (248 mm or 254 mm)
156027-02	ST-BC-12 (Holds 12-10" or 4-30" Cartridges)**	84 gpm (318 Lpm)	39.75" x 10" (1,010 mm x 254 mm)	3" (76 mm)	9.75" or 10" (248 mm or 254 mm)
156028-02	ST-BC-16 (Holds 16-10" or 4-40" Cartridges)**	110 gpm (416 Lpm)	49.75" x 10" (1,264 mm x 254 mm)	3" (76 mm)	9.75" or 10" (248 mm or 254 mm)
156032-02	ST-BC-20 (Holds 20-10" or 5-40" Cartridges)**	125 gpm (473 Lpm)	49.75" x 10" (1,264 mm x 254 mm)	2-1/2" (64 mm)	9.75" or 10" (248 mm or 254 mm)

^{*}Based on sediment removal with a 25-micron filter cartridge and 1 PSIG initial clean pressure drop.

NOTES: Maximum cartridge diameter 3" (76 mm). Not recommended for applications with TDS or Chlorides >1000 ppm and/or pH <5.0. Use of this product in these conditions will void the limited warranty. Consult factory for product modifications for these conditions.

CAUTION: Protect against freezing to prevent cracking of the filter and water leakage.

WARNING: If pressure exceeds 125 psi (8.62 bar) at any time, a pressure regulator must be used. Do not use water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.

ACCESSORIES

PART #	DESCRIPTION			
143218	Gasket for STBC Series			
243316	ST-BC Gasket, Silicone			
243317	ST-BC Gasket, Teflon®			
243318	ST-BC Gasket, Viton®			
243319	ST-BC 1/4" Vent Plug			
243320	ST-BC 1/2" Drain Plug			
243321	ST-BC-4 Center Rod			
243322	ST-BC-8 Center Rod			
243323	ST-BC-12 Center Rod			
243324	ST-BC-16 Center Rod			
243325	ST-BC-20 Center Rod			
143221	ST-BC /Cover Clamp			
243326	ST-BC Head			
243327	ST-BC Top Plate, 4-Stack			
243328	ST-BC-20 Top Plate, 5-Stack			
243329	ST-BC Top Plate Bushing			
243330	ST-BC 3/8" Plate Knob 4-Stack			
243331	ST-BC-20 1/2" Plate Knob			
243332	ST-BC Top Plate Retaining Ring			
243333	ST-BC T-bolt W/handle for Clamp			
243334	ST-BC-4 Cartridge V-Post			
243335	ST-BC 8 Cartridge V-Post			
243336	ST-BC-12 & 16 Cartridge V-Post			
243337	ST-BC-20 Cartridge V-Post			





FILTRATION & PROCESS

5730 NORTH GLEN PARK ROAD, MILWAUKEE, WI 53209
P: 262.238.4400 | F: 262.238.4404 | WWW.PENTAIRAQUA.COM | CUSTOMER CARE: 800.279.9404

Telefone: 41 3081-3050

All Pentair trademarks and logos are owned by Pentair, Inc. or its affiliates. All other registered and unregistered trademarks and logos are the property of their respective owners. Because we are continuously improving our products and services, Pentair reserves the right to change specifications without prior notice.

Pentair is an equal opportunity employer.

310057 REV C MR14 © 2014 Pentair Residential Filtration, LLC. All Rights Reserved.

^{**}Number of cartridges refers to the number of 9.75" (248 mm) or 10" (254 mm) cartridges which are configured around the housing times the number of cartridges that may be stacked.