

## Enclosed Filtration System BECO INTEGRA® LAB 220 S



### Large Cake Frame Chamber

BECO INTEGRA LAB 220 S from Eaton's Begerow Product Line was developed especially for processing small quantities in laboratories and in technical colleges as well as for the production of small batches and for upscaling in the beverage and food industries, for bio-engineering, pharmaceuticals as well as the chemical and cosmetic industries.

The enclosed filtration system's special design of two round, vertical filter elements on the left and right sides of the filter frame, makes it possible to transfer the test results directly from the laboratory or research center to process equipment such as the BECO INTEGRA PLATE enclosed plate and frame filter.

#### Function Principle

The BECO INTEGRA LAB 220 S uses depth filtration sheets to remove undesirable suspended solids, sediments or microorganisms from the liquid/suspension. For this purpose, the liquid is fed into a cake frame. The pressure difference between the in- and outflow causes the liquid to flow through the depth filter sheet. As a result, depending upon application, it emerges either clarified or sterilized. The filtrate discharges through the outflow, collects in the drainage grooves and flows to the filtrate outlet.

An O-ring located behind the sheet frame reliably prevents any emissions from the filtered product from reaching the surrounding environment, even in difficult filtration applications.

By using two different depth filter sheets, for example coarse and fine filtration, the system combines multiple steps such as pre-filtration and sterilizing filtration into one filtration step.

#### Technical Data

<b>Max. permissible operating pressure:</b>	58 psi (400 kPa/4 bar)
<b>Max. permissible differential pressure:</b>	43.5 psi (300 kPa/3 bar)
<b>Max. permissible operating temperature:</b>	284 °F (140 °C)



#### Filter

<b>Depth filter sheet size:</b>	Ø 8.74" (222 mm)
<b>Filter surface:</b>	0.33 ft² (0.031 m²)/ depth filter sheet
<b>Number of depth filter sheets</b>	
<b>Single stage filtration:</b>	1 or 2 sheets
<b>Two stage filtrations:</b>	1 x 2 or 2 x 2 sheets
<b>Cake frame width:</b>	1.58" (40 mm)
<b>Max. cake volume:</b>	0.33 gal (1.25 l)

Description	Article no.
BECO INTEGRA LAB 220 S	59262106
Lever for round filter	P7800105
Star knob 50 x M10 (knurled nut)	P7800101

Description	EPDM	Silicone	Viton	FEP coated
O-ring round filter BECO INTEGRA LAB 220	59262117	P7800302	59262118	P7800304

#### Materials

<b>Product contacting parts:</b>	Stainless steel AISI 316L/AISI 316Ti
<b>Others:</b>	Stainless steel AISI 304
<b>Gaskets, O-rings:</b>	EPDM, Silicone, Viton, FEP coated

#### Connections

<b>Inlet/outlet:</b>	Hose nozzle for hose inside Ø 0.51" (13 mm)
<b>Ventilation:</b>	Air relief cock and manometer 0 – 87 psi (0 – 600 kPa/0 – 6 bar)

#### North America - HQ

44 Apple Street,  
Tinton Falls, NJ 07724  
Toll Free: 800 656-3344  
(North America Only)  
Voice: +1 732 212-4700

#### Europe/Africa/Middle East

Auf der Heide 2  
53947 Nettersheim, Germany  
Voice: +49 2486 809-0

#### Internormen Product Line

Friedensstraße 41  
68804 Altlussheim, Germany  
Voice: +49 6205 2094-0

#### Begerow Product Line

An den Nahewiesen 24  
55450 Langenlonsheim, Germany  
Voice: +49 6704 204-0

#### Brazil

Av. Julia Gaioli, 474 - Bonsucesso  
07251-500 - Guarulhos  
Brazil  
Voice: +55 11 2465 8822

#### China

No. 7 Lane 280 Linhong Road,  
Changning District,  
Shanghai 200335, China  
Voice: +86 21 5200 0422

#### Singapore

4 Loyang Lane #04-01/02  
Singapore 508914  
Voice: +65 6825 1668

For more information, please e-mail us  
at [filtration@eaton.com](mailto:filtration@eaton.com) or visit us online  
at [eaton.com/filtration](http://eaton.com/filtration) for a complete list  
of Eaton's filtration products.

Not all products in Eaton's Begerow  
Product Line are available in all regions.  
Please contact your local Eaton office to  
determine availability.

© 2012 Eaton Corporation. All Rights Reserved. All  
trademarks and registered trademarks are the  
property of their respective owners.

All information and recommendations appearing in  
this brochure concerning the use of products  
described herein are based on tests believed to be  
reliable. However, it is the user's responsibility to  
determine the suitability for his own use of such  
products. Since the actual use by others is beyond  
our control, no guarantee, expressed or implied, is  
made by Eaton as to the effects of such use or the  
results to be obtained. Eaton assumes no liability  
arising out of the use by others of such products.  
Nor is the information herein to be construed as  
absolutely complete, since additional information  
may be necessary or desirable when particular or  
exceptional conditions or circumstances exist or  
because of applicable laws or government  
regulations.



Powering Business Worldwide

EN  
1 A 2.6.17  
12-2012