HP LaserJet P4515n, P4515tn and P4515x Printer

HP's fastest monochrome LaserJet printer combines high-productivity printing with robust security features for exceptional performance.

Product pointers

- With first-page-out as fast as 8.5 seconds from low power mode, and print speed of up to 60 pages-per-minute (ppm), A4¹, print job can be completed quickly, improving workgroup productivity.
- Secure business-critical data with security features: PIN and Pull
 printing, IPsec encryption and device authentication through
 802.1X networking. Simplify fleet management with HP Web
 Jetadmin and let your business enjoy secured results effectively.
- Best user experience with intuitive "Show-Me-How" features that help to simplify configuration, troubleshooting and maintenance. Optimise printer capabilities with robust paper handling and finishing features, and expanded media support.
- HP's latest advancement in toner technology provides consistently outstanding print quality at the print speeds required in robust business printing environments.
- With a 540 MHz processor, 128 MB RAM memory, and a powerful HP Jetdirect Gigabit Ethernet Embedded Print Server, the printer is designed to process jobs quickly, providing a fast return to the print job's application, for increased uptime.
- ¹ Exact speed depends on system configuration, software programs and document complexity.

Ordering information

Model Number	P4515n	P4515tn	P4515x
Product No.	CB514A	CB515A	CB516A

Compatibility

Operating System	P4515n	P4515tn	P4515x	
Standard Desktop				
Windows NT 4.0	•	•	•	
Windows 2000	•	•	•	
Windows XP	•	•	•	
Windows Vista®	•	•	•	
Mac OS 09/10	•	•	•	
Standard Network				
Windows NT 4.0	•	•	•	
Windows 2000	•	•	•	
Windows XP/XP 64-bit	•	•	•	
Windows Server 2003	•	•	•	
Windows Vista®	•	•	•	
UNIX (HP-UX, Solaris)	•	•	•	
Linux (Red Hat, SuSE)	•	•	•	
Other	Novell NetW	are 3.2, 4.2, 5.x, 6.:	x; Apple Mac OS 8	8.6

and later; Red Hat Linux 6.x and later; SuSE Linux 6.x and later; HP-UX 10.20, 11.x; Solaris 2.5x, 2.6, 7, 8, 9, 10 (SPARC systems only); IBM AIX 3.2.5 and later; MPE-ix



HP Laserlet P4515n Printer

In the box

All Models:

- Power cord
- Ultraprecise print cartridge
- Getting started guide
- · Software and electronic user guide on CD-ROMs

Software

Print drivers

Shipping weight and shipping dimensions

P4515n
 P4515tn
 P4515tn
 P4515tn
 P4515tn
 P4515x
 P4515x
 P4515x

Networking solutions

See Connectivity Products for complete information.

Connectivity

HP Jetdirect internal:	
630n, IPv6/Gigabit Ethernet	J7997G
635n, IPv6/Ipsec Gigabit	J7961G

HP Jetdirect external:
170x, 10 Base-T (parallel)
300x, 10/100 Base-TX (parallel)
510x, 10/100 Base-TX (parallel)

J3258G J3263G J7983G

Warranty and support

Standard warranty¹

• Minimum 1 year standard

HP Care Pack services

Please check with your local HP resellers or local HP offices for details and availability.

See $\underline{\mathsf{HP}\ \mathsf{Care}\ \mathsf{Pack}}$ for complete information.

Warranty may vary according to countries. Please check with your local HP sales office or your nearest HP authorised dealer for details.

Datasheet publication number: 200080057-EEP

Model specifications, schematic and memory map

• Shaded rows indicate variations between models

Model Number	P4515n	P4515tn	P4515x		
Product Number	CB514A	CB515A	CB516A		
Print Speed Black,	Up to 62 ppm (letter),	Up to 62 ppm (letter),	Up to 62 ppm (letter),		
Best Quality ¹	Up to 60 ppm (A4)	Up to 60 ppm (A4)	Up to 60 ppm (A4)		
irst Page Out	As fast as 8.5 seconds from Ready mode; Time To Completion for a typical office print job: as fast as 16 seco				
Processor	540 MHz	540 MHz	540 MHz		
Outy Cycle, Monthly	Up to 275,000 pages	Up to 275,000 pages	Up to 275,000 pages		
aper Trays, Std	2	3	3		
Paper Trays, Max	5	5	5		
nput Capacity, Std	100-sheet multipurpose tray 1, 500-sheet tray 2	100-sheet multipurpose tray 1, 500-sheet tray 2, 500-sheet tray 3	100-sheet multipurpose tray 1, 500-sheet tray 2, 500-sheet tray 3		
nput Capacity, Max	3,100 sheets	3,100 sheets	3,100 sheets		
Output Capacity, Std	100-sheet rear output bin, 500-shee	et top output bin			
Output Capacity, Max	100-sheet rear output bin, 500-sheet top output bin				
invelope Input, Std	10	10	10		
nvelope Feeder	Optional, 75 envelopes	Optional, 75 envelopes	Optional, 75 envelopes		
Ouplex Printing	Manual (driver support provided)	Manual (driver support provided)	Automatic (standard)		
Media Sizes, Std	Multipurpose tray 1: letter, legal, executive, statement, 8.5 x 13 inches; A4, A5, B5 (JIS), double postcard (JIS), 16K, executive (JIS), envelope (Com 10, Monarch No. 7 3/4, DL ISO, C5 ISO, B5 ISO); input trays 2 and 3: letter, legal, executive, statement, 8.5 x 13 inches; A4, A5, B5 (JIS), 16K, executive (JIS) Multipurpose tray 1: custom: 76 x 127 mm (3 x 5 inches) to 216 x 336 mm (8.5 x 14 inches); Input trays 2 and 3				
Media Sizes Custom	Multinurnose tray 1: custom: 76 v	127 mm /3 v 5 inches) to 216 v 356 mm	18.5 x 1.4 inches): Input travs 2 and		
Media Sizes, Custom			(8.5 x 14 inches); Input trays 2 and		
Media Sizes, Custom	148 x 210 mm (5.8 x 8.3 inches) t	o 216 x 356 mm (8.5 x 14 inches) nin, preprinted, prepunched, recycled, rou			
Media Types	148 x 210 mm (5.8 x 8.3 inches) t Paper (bond, colour, letterhead, plc cardstock, transparencies, user-defi	o 216 x 356 mm (8.5 x 14 inches) sin, preprinted, prepunched, recycled, rouned m ² ; input trays 2 and 3, optional 500-she	ugh, light), envelopes, labels,		
Media Types Media Weights	148 x 210 mm (5.8 x 8.3 inches) t Paper (bond, colour, letterhead, plc cardstock, transparencies, user-defi Multipurpose tray 1: 60 to 200 g/t	o 216 x 356 mm (8.5 x 14 inches) sin, preprinted, prepunched, recycled, rouned m ² ; input trays 2 and 3, optional 500-she	ugh, light), envelopes, labels,		
Media Types Media Weights Memory, Std	148 x 210 mm (5.8 x 8.3 inches) t Paper (bond, colour, letterhead, plc cardstock, transparencies, user-defi Multipurpose tray 1: 60 to 200 g/t Optional envelope feeder: 75 to 10	o 216 x 356 mm (8.5 x 14 inches) iin, preprinted, prepunched, recycled, rou ned m²; input trays 2 and 3, optional 500-she 05 g/m²	ugh, light), envelopes, labels, et feeder: 60 x 120 g/m²;		
Media Types Media Weights Memory, Std Memory, Max	148 x 210 mm (5.8 x 8.3 inches) the Paper (bond, colour, letterhead, placardstock, fransparencies, user-defi Multipurpose tray 1: 60 to 200 g/t Optional envelope feeder: 75 to 10 128 MB	o 216 x 356 mm (8.5 x 14 inches) iin, preprinted, prepunched, recycled, rou ned n²; input trays 2 and 3, optional 500-she 05 g/m² 128 MB 640 MB	ugh, light), envelopes, labels, et feeder: 60 x 120 g/m²;		
Media Types Media Weights Memory, Std Memory, Max Typefaces	148 x 210 mm (5.8 x 8.3 inches) the paper (bond, colour, letterhead, placardstock, transparencies, user-defit Multipurpose tray 1: 60 to 200 g/r Optional envelope feeder: 75 to 10 128 MB 640 MB 80 HP font set (plus Greek, Hebrew	o 216 x 356 mm (8.5 x 14 inches) irin, preprinted, prepunched, recycled, rouned m²; input trays 2 and 3, optional 500-she 15 g/m² 128 MB 640 MB 4, Cyrillic, Arabic) xternal and 2 internal Host USB 2.0-like p	ugh, light), envelopes, labels, et feeder: 60 x 120 g/m²; 128 MB 640 MB		
Media Types Media Weights Memory, Std Memory, Max ypefaces Connectivity, Std	148 x 210 mm (5.8 x 8.3 inches) t Paper (bond, colour, letterhead, pla cardstock, transparencies, user-defi Multipurpose tray 1: 60 to 200 g/r Optional envelope feeder: 75 to 10 128 MB 640 MB 80 HP font set (plus Greek, Hebrew I Hi-speed USB 2.0, 1 EIO slot, 1 e	o 216 x 356 mm (8.5 x 14 inches) inin, preprinted, prepunched, recycled, rouned n²; input trays 2 and 3, optional 500-she 105 g/m² 128 MB 640 MB r, Cyrillic, Arabic) xternal and 2 internal Host USB 2.0-like p	ugh, light), envelopes, labels, et feeder: 60 x 120 g/m²; 128 MB 640 MB		
Media Types Media Weights Memory, Std Memory, Max Typefaces Connectivity, Std Connectivity, Opt	148 x 210 mm (5.8 x 8.3 inches) the Paper (bond, colour, letterhead, placardstock, transparencies, user-defit Multipurpose tray 1: 60 to 200 g/t Optional envelope feeder: 75 to 10 128 MB 640 MB 80 HP font set (plus Greek, Hebrew 1 Hispeed USB 2.0, 1 EIO slot, 1 e HP Jetdirect Gigabit Ethernet ember	o 216 x 356 mm (8.5 x 14 inches) inin, preprinted, prepunched, recycled, rouned n²; input trays 2 and 3, optional 500-she 105 g/m² 128 MB 640 MB r, Cyrillic, Arabic) xternal and 2 internal Host USB 2.0-like p	ugh, light), envelopes, labels, et feeder: 60 x 120 g/m²; 128 MB 640 MB		
Media Types Media Weights Memory, Std Memory, Max Typefaces Connectivity, Std Connectivity, Opt Prints Colour	148 x 210 mm (5.8 x 8.3 inches) the paper (bond, colour, letterhead, placardstock, transparencies, user-defit Multipurpose tray 1: 60 to 200 g/r Optional envelope feeder: 75 to 10 128 MB 640 MB 80 HP font set (plus Greek, Hebrew I Hi-speed USB 2.0, 1 EIO slot, 1 e HP Jetdirect Gigabit Ethernet embet HP Jetdirect (EIO) internal and exter No	o 216 x 356 mm (8.5 x 14 inches) inin, preprinted, prepunched, recycled, rot ned n²; input trays 2 and 3, optional 500-she 55 g/m² 128 MB 640 MB v, Cyrillic, Arabic) xternal and 2 internal Host USB 2.0-like p dded print server	ugh, light), envelopes, labels, et feeder: 60 x 120 g/m²; 128 MB 640 MB ports for third-party connection,		
Media Types Media Weights Memory, Std Memory, Max ypefaces Connectivity, Std Connectivity, Opt Prints Colour echnology, Black Print Resolution	148 x 210 mm (5.8 x 8.3 inches) the paper (bond, colour, letterhead, placardstock, transparencies, user-defi Multipurpose tray 1: 60 to 200 g/r Optional envelope feeder: 75 to 10 128 MB 640 MB 80 HP font set (plus Greek, Hebrew I Hi-speed USB 2.0, 1 EIO slot, 1 e HP Jetdirect Gigabit Ethernet ember HP Jetdirect (EIO) internal and exter No Up to 1200 x 1200 dpi; HP Image	o 216 x 356 mm (8.5 x 14 inches) irin, preprinted, prepunched, recycled, rouned m²; input trays 2 and 3, optional 500-she 35 g/m² 128 MB 640 MB to Cyrillic, Arabic) sternal and 2 internal Host USB 2.0-like padded print server nol print server	ugh, light), envelopes, labels, et feeder: 60 x 120 g/m²; 128 MB 640 MB ports for third-party connection,		
Media Types Media Weights Memory, Std Memory, Max Typefaces Connectivity, Std Connectivity, Opt Prints Colour Technology, Black Print Resolution Print Languages, Std	148 x 210 mm (5.8 x 8.3 inches) the paper (bond, colour, letterhead, placerdstock, transparencies, user-defined Multipurpose tray 1: 60 to 200 g/r Optional envelope feeder: 75 to 10 128 MB 640 MB 80 HP font set (plus Greek, Hebrew I Hisspeed USB 2.0, 1 EIO slot, 1 e HP Jetdirect Gigabit Ethernet ember HP Jetdirect (EIO) internal and external No Up to 1200 x 1200 dpi; HP Image HP PCL 6, HP PCL 5e, HP PostScrip	o 216 x 356 mm (8.5 x 14 inches) irin, preprinted, prepunched, recycled, rouned m²; input trays 2 and 3, optional 500-she 35 g/m² 128 MB 640 MB v, Cyrillic, Arabic) saternal and 2 internal Host USB 2.0-like patent server No REt, HP 300 dpi, HP 600 dpi, HP FastRes t Level 3 emulation, direct PDF (v1.4) prin	ugh, light), envelopes, labels, et feeder: 60 x 120 g/m²; 128 MB 640 MB ports for third-party connection,		
Media Types Media Weights Memory, Std Memory, Max Typefaces Connectivity, Std Connectivity, Opt Prints Colour Technology, Black	148 x 210 mm (5.8 x 8.3 inches) the paper (bond, colour, letterhead, placardstock, transparencies, user-defit Multipurpose tray 1: 60 to 200 g/r Optional envelope feeder: 75 to 10 128 MB 80 HP font set (plus Greek, Hebrew I Hi-speed USB 2.0, 1 EIO slot, 1 e HP Jetdirect (EIO) internal and exter No Up to 1200 x 1200 dpi; HP Image HP PCL 6, HP PCL 5e, HP PostScrip recommended)	o 216 x 356 mm (8.5 x 14 inches) irin, preprinted, prepunched, recycled, rouned m²; input trays 2 and 3, optional 500-she 35 g/m² 128 MB 640 MB v, Cyrillic, Arabic) saternal and 2 internal Host USB 2.0-like patent server No REt, HP 300 dpi, HP 600 dpi, HP FastRes t Level 3 emulation, direct PDF (v1.4) prin	ugh, light), envelopes, labels, et feeder: 60 x 120 g/m²; 128 MB 640 MB ports for third-party connection, No		

HP LaserJet P4515 Printer series





CB522A

CB523A

Supplies and accessories

See Original HP Printing Supplies for complete media compatibility and additional information on supplies. See HP Accessories for more information on connectivity, paper-handling solutions and printer memory.

Print Cartridges

- HP LaserJet Black Print Cartridge (10,000 pages¹)
- HP LaserJet Black Print Cartridge (24,000 pages¹) CC364X

Media

For a range of HP Business Communications See Original HP Printing Supplies for complete information:

- HP LaserJet Paper
- HP Inkjet Paper

Accessories

Stapler/Stacker

- HP LaserJet 500-sheet Input Tray CB518A and Feeder
- HP LaserJet Automatic Duplexer for Two-sided Printing CB519A
- HP LaserJet 500-sheet 5-bin Mailbox CB520A • HP LaserJet 500-sheet
- HP LaserJet 1.500-sheet High Capacity Input Tray
- HP LaserJet 75-sheet Envelope Feeder CB524A • HP LaserJet Printer Stand CB525A
- HP LaserJet 1,000 Staple Cartridge pack (3 cartridges by 1,000) Q3216A

- HP LaserJet Printer
- Maintenance Kit (110V) CB388A

• HP LaserJet Printer Maintenance Kit (220V) CB389A

Memory and mass storage

- HP 64 MB DDR2 144-pin x32 CC413A
- HP 128 MB DDR2 144-pin x32 CC414A
- HP 256 MB DDR2 144-pin x32 CC415A
- HP 512 MB DDR2 144-pin x32 CE483A
- HP High Performance Serial J7989G ATA Hard Disk

Average cartridge yield. Declared yield value in accordance with ISO/IEC 19752.