

## Stormcote Smooth Masonry Paint

<b>Product Description</b>	<b>A water based acrylic, exterior masonry paint.</b>			
<b>Features &amp; Use</b>	<ul style="list-style-type: none"> <li>• Excellent resistance to dirt pick-up</li> <li>• Outstanding, proven durability combined with an attractive appearance with an elegant low-sheen finish. It is self-priming on porous surfaces with excellent obliterating power</li> <li>• Algae and fungi are controlled by a wide spectrum biocide</li> <li>• Use for the protection of interior and exterior ceilings and walls in e.g. kitchens and bathrooms.</li> <li>• Suitable for plaster, cement, concrete and most other porous surfaces where a long-life durable coating is required, with the ability to fill minor imperfections and resist structural movements</li> </ul>			
<b>Approvals/ Certification</b>	Please consult Axalta Coating Systems			
<b>Finish</b>	Matt			
<b>Volume Solids</b>	30 ± 2% (varies with colour)			
<b>VOC Content</b>	5 ± 20 g/litre (varies with colour)			
<b>Film Thickness Range And Coverage</b>		<b>Dry Film Thickness</b>	<b>Wet Film Thickness</b>	<b>Theoretical Coverage</b>
	<b>Typical</b>	45 µm	140 µm	7.1 m <sup>2</sup> /litre
	Practical coverage depends on the application method, painting conditions and the shape and roughness of the surface to be coated			
<b>Drying Times</b>	Applied to 45 microns DFT	<b>+10°C</b>	<b>+23°C</b>	
	<b>Dust Free</b>		45 min	30 min
	<b>Hard Dry</b>		3 hr	2 hr
	<b>Overcoating</b>	Minimum	3 hr	2 hr
Maximum		Indefinite if clean and sound		
	Drying and recoating times are related to the film thickness, temperature, the relative humidity of the air and ventilation			
<b>Colours</b>	White, Magnolia plus limited range			
<b>Product Code</b>	<b>01SST-</b>			
<b>SG</b>	1.30 kg/lit (varies with colour)			
<b>Storage Conditions</b>	Store in dry, cool conditions and protect from frost			
<b>Shelf Life</b>	Minimum 12 months if stored as above in unopened containers			
<b>Flash Point</b>	23-60°C			

# Stormcote Smooth Masonry Paint

<b>Surface Preparation</b>	<ul style="list-style-type: none"> <li>Surfaces should be clean, dry and free from all grease, oil, loose material and general contamination</li> <li>Unsound surfaces should be scraped back to firm edge</li> <li>If algal or fungal contamination is present, wash with a bleach solution (observing necessary safety precautions)</li> <li>Prime prepared surfaces with Stormcote Acrylic Sealer or Stormcote Stabilising Sealer</li> </ul>				
<b>Mixing</b>	Must be mixed thoroughly before use. Agitate periodically to ensure paint remains homogeneous.				
<b>Thinner</b>	Clean Water		<b>Equipment Cleaner</b> Clean Water		
<b>Application Conditions</b>	Only apply in conditions of good ventilation which must be maintained during drying and curing. Do not apply when rain, mist, sleet or snow are imminent. During application and drying time of the paint coating, the surface should be dry, the Relative Humidity should not exceed 85% and the surface temperature should remain at least 3°C above the dew point. Paint temperature should ideally be at a minimum of 15°C.				
<b>Application Methods</b>	<b>Method</b>	<b>Airless Spray</b>	<b>Conventional Spray</b>	<b>Brush</b>	<b>Roller</b>
		Yes	Yes	Yes	Yes
<b>Product Notes</b>	<ul style="list-style-type: none"> <li>Protect from frost and store above 5°C. Do not use below 5°C</li> <li>Do not apply to damp or frosted surfaces</li> <li>This coating has not been tested to the standard of the new regulation 7(2) of the Building Regulations 2010, which came into force in Dec 2018</li> </ul>				
<b>Health &amp; Safety</b>	Containers are provided with safety labels which should be observed. Further information about hazardous influences and protection are detailed in individual Product Safety Data Sheets. A Safety Data Sheet for this product is available on request from Axalta Coating Systems.				

The information provided herein corresponds to our knowledge on the subject at the date of its publication. This information may be subject to revision as new knowledge and experience becomes available. The data provided fall within the normal range of product properties and relate only to the specific material designated; these data may not be valid for such material used in combination with any other materials or additives or in any process, unless expressly indicated otherwise. The data provided should not be used to establish specification limits or used alone as the basis of design; they are not intended to substitute for any testing you may need to conduct to determine for yourself the suitability of a specific material for your particular purposes. Since Axalta cannot anticipate all variations in actual end-use conditions Axalta makes no warranties and assumes no liability in connection with any of this information. Nothing in this publication is to be considered as a license to operate under or a recommendation to infringe any patent rights. This product is for professional use only.