

## PC99 Anti-Vandal Coating

<b>Product Description</b>	<b>A thick-film, non-setting coating based on petroleum derivatives</b> for use as an anti-intruder coating.			
<b>Features &amp; Use</b>	<ul style="list-style-type: none"> <li>• A non-oxidising, non-setting coating recommended by various police forces as an anti-intruder coating and to act as a deterrent to burglars and vandals</li> <li>• Has a wide working temperature from -20°C up to 60°C</li> <li>• Can be applied to most surfaces, is low odour and solvent free</li> <li>• For use on drain pipes, sills, tops of wall and fences, garage and porch roofs, flat roofs, trees (to discourage theft of eggs), electricity pylons (to deter access to dangerous areas), telegraph poles and lamp posts (to deter climbing)</li> </ul>			
<b>Approvals/ Certification</b>	Please consult Axalta Coating Systems			
<b>Finish</b>	Slight sheen			
<b>Volume Solids</b>	100%			
<b>VOC Content</b>	0 g/litre			
<b>Film Thickness Range And Coverage</b>		<b>Dry Film Thickness</b>	<b>Wet Film Thickness</b>	<b>Theoretical Coverage</b>
	<b>Typical</b>	400 µm	400 µm	2.5 m <sup>2</sup> /litre
	Practical coverage depends on the application method, painting conditions and the shape and roughness of the surface to be coated			
<b>Drying Times</b>	Applied to (n/a) microns DFT	<b>+10°C</b>	<b>+23°C</b>	<b>+35°C</b>
	<b>Dust Free</b>		<b>This product does not dry</b>	
	<b>Hard Dry</b>			
	<b>Overcoating</b>	Minimum	This product is not overcoatable	
		Maximum		
	Drying and recoating times are related to the film thickness, temperature, the relative humidity of the air and ventilation			
<b>Colours</b>	Black Grey, Red			
<b>Product Code</b>	<b>06P99</b>			
<b>SG</b>	1.00 kg/lt			
<b>Storage Conditions</b>	Store in dry, cool conditions and protect from frost			
<b>Shelf Life</b>	Minimum 12 months if stored as above in unopened containers			
<b>Flash Point</b>	Above 60°C			



# PC99 Anti-Vandal Coating

Issue Date: Apr 2018  
Page 2 of 2

<b>Surface Preparation</b>	<ul style="list-style-type: none"> <li>All surfaces to be coated should be dry and cleaned as necessary to remove all oil, grease, salts or other contamination</li> <li>Wire brush to remove loose dirt, existing paint flakes and any rust or corrosion products</li> </ul>														
<b>Mixing</b>	Must be mixed thoroughly before use.														
<b>Thinner</b>	Do not thin <b>Equipment Cleaner No.3 Thinner</b>														
<b>Application Conditions</b>	Only apply in conditions of good ventilation which must be maintained during drying and curing. Do not apply when rain, mist, sleet or snow are imminent. During application and drying time of the paint coating, the surface should be dry, the Relative Humidity should not exceed 85% and the surface temperature should remain at least 3°C above the dew point. Paint temperature should ideally be at a minimum of 15°C.														
<b>Application Methods</b>	<table border="1" data-bbox="451 790 1489 925"> <thead> <tr> <th data-bbox="451 790 675 869">Method</th> <th data-bbox="675 790 922 869">Airless Spray</th> <th data-bbox="922 790 1169 869">Conventional Spray</th> <th data-bbox="1169 790 1337 869">Brush</th> <th data-bbox="1337 790 1489 869">Roller</th> </tr> </thead> <tbody> <tr> <td data-bbox="451 869 675 925"></td> <td data-bbox="675 869 922 925">No</td> <td data-bbox="922 869 1169 925">No</td> <td data-bbox="1169 869 1337 925">Yes</td> <td data-bbox="1337 869 1489 925">No</td> </tr> </tbody> </table> <ul style="list-style-type: none"> <li>Brush – as supplied</li> </ul>					Method	Airless Spray	Conventional Spray	Brush	Roller		No	No	Yes	No
Method	Airless Spray	Conventional Spray	Brush	Roller											
	No	No	Yes	No											
<b>Product Notes</b>	<ul style="list-style-type: none"> <li>Do not thin. If the product appears too thick to apply it may be too cold - store it in a warm place (observing all Health and Safety requirements) until a suitable consistency is achieved</li> <li>Do not use on surfaces likely to be used by authorised personnel. It is recommended to apply the product at least 7 feet (2.3 m) above ground level.</li> <li>Do not apply other coatings over PC99</li> <li>To remove the coating, use scrapers and washing of the surface with Thinner No.3 (ensure sufficient ventilation and observe Health and Safety procedures)</li> <li>It is recommended to erect a Warning Notice that a non-setting product is present</li> </ul>														
<b>Health &amp; Safety</b>	Containers are provided with safety labels which should be observed. Further information about hazardous influences and protection are detailed in individual Product Safety Data Sheets. A Safety Data Sheet for this product is available on request from Axalta Coating Systems.														

The information provided herein corresponds to our knowledge on the subject at the date of its publication. This information may be subject to revision as new knowledge and experience becomes available. The data provided fall within the normal range of product properties and relate only to the specific material designated; these data may not be valid for such material used in combination with any other materials or additives or in any process, unless expressly indicated otherwise. The data provided should not be used to establish specification limits or used alone as the basis of design; they are not intended to substitute for any testing you may need to conduct to determine for yourself the suitability of a specific material for your particular purposes. Since Axalta cannot anticipate all variations in actual end-use conditions Axalta makes no warranties and assumes no liability in connection with any of this information. Nothing in this publication is to be considered as a license to operate under or a recommendation to infringe any patent rights. This product is for professional use only.