

# KARAM FLUSH MOUNT CEILING

## PRODUCT FEATURES



## LAMPING

Includes 22 watt, 587 net lumen, 3000K LED module or Warm Color Dimming 3000K-2200K LED module. Dimmable with low-voltage electronic dimmer.

Concrete



Concrete

White

## ORDERING INFORMATION

700FMKRM COLOR	LAMP
W WHITE	-LED930 LED 90 CRI 3000K 120V

700FMKRM \_\_\_\_\_

JOB NAME \_\_\_\_\_

NOTES \_\_\_\_\_

\_\_\_\_\_




# KARAM FLUSH MOUNT CEILING



## SPECIFICATIONS

HARDWARE MATERIAL	
SHADE MATERIAL	
NET WEIGHT	4.95 lbs
HEIGHT	
WIDTH	
LENGTH	
UP LIGHT / DOWN LIGHT / BOTH?	
WET LISTED	
DAMP LISTED	
DRY LISTED	
WALL / CEILING MOUNT	
SLOPED CEILING ADAPTABLE?	No
GENERAL LISTING	ETL Listed
INCLUDES	



## LAMPING SPECIFICATIONS

	LED LAMP	INTEGRATED LED	NON LED	NO LAMP
DELIVERED LUMENS	1125			
WATTS	24			
MAX WATTAGE PER BULB	24W			
INPUT VOLTAGE				
DIMMING TYPE*	ELV			
CCT	3000K			
CRI	90 CRI			
LED LIFETIME				
L70				
AVERAGE BULB HOURS				
FIELD SERVICEABLE LED				
LAMP BASE	E26 Medium Base			
LAMP SHAPE	LED Bi-Pin			
LAMP INCLUDED?	Y			
WARRANTY**	1 Year			

\*Dimming information available at [www.techlighting.com/Downloads#dimming](http://www.techlighting.com/Downloads#dimming)  
 \*\* Visit [techlighting.com](http://techlighting.com) for specific warranty limitations and details.

## T20 / T24 INFORMATION

	Integrated LED	Replacement LED Lamp	No Lamp *
This product can be used to comply with California Building Energy Efficiency Standards 2016 <b>Title 24</b> Part 6.			
This product can be used to comply with California Appliance Efficiency Standards 2016 <b>Title 20</b> and may be shipped to and sold in California.			

\* If a light fixture or component does not include a lamp or light source, it is the responsibility of the customer to select a lamp that meets the T24 and T20 requirements.