
RECTANGLE STEP LIGHTS 12V

4011

LANDSCAPE LIGHTING



PRODUCT DESCRIPTION

Horizontal rectangle step light designed for safety and style on stairways, patios, decks, balcony areas, walkways and building perimeters.

Features an architectural design. Energy efficient for long-lasting outdoor lighting solutions. Creates an attractive, romantic impression at night.

FEATURES

Solid diecast brass, corrosion resistant aluminum alloy, or cast stainless steel construction

Color Temp

- IP66 rated, Protected against high-pressure water jets
- · Conveniently adapts into existing 12V system
- Invisible hardware
- Maintains constant lumen output against voltage drop
- UL 1838 Listed

SPECIFICATIONS

Input: 9-15VAC (Transformer is required)

Power: 2W / 3.1VA

CRI: 90

Mounting: Fits into $2'' \times 4''$ J-Box

Lumens

with minimum inside dimensions of $3"L \times 2"W \times 2"H$

Includes bracket for J-Box mount.

Rated Life: 60,000 hours

ORDERING NUMBER

		COIOI	Tellip	CINI	1 11 11 31 1		Luillella
					BBR	Bronze on Brass	17
		27	2700K	90	BK	Black on Aluminum	17
		-/	270011	70	BZ	Bronze on Aluminum	17
					WT	White on Aluminum	38
4011	12V		3000K	90	BBR	Bronze on Brass	17
					BK	Black on Aluminum	17
		30			BZ	Bronze on Aluminum	17
					WT	White on Aluminum	38
					SS	Cast Stainless Steel	23
		АМ	Amber	-	BBR	Bronze on Brass	11
					BK	Black on Aluminum	11
					BZ	Bronze on Aluminum	11
					WT	White on Aluminum	23
					SS	Cast Stainless Steel	14

Finish

4011-____

Example: 4011-30BK



LANDSCAPE LIGHTING

Magnetic Transformers

Stainless Steel, 12-15V output, IP65 rated, UL 1838 listed See transformer spec sheet for details and its accessories

9075-TRN-SS *75W Max*

9150-TRN-SS *150W Max*

9300-TRN-SS 300W Max

9600-TRN-SS 600W Max



TESTED MAGNETIC LOW VOLTAGE(MLV) DIMMERS


Luminaire	Dimmer								
	Manufacturer	Family	Model	Power Rating	Range*	Note			
4011	Lutron	Diva	DVLV-600	600W	23% - 100%				
		Skylark	SLV-600P	600W	17% - 100%	Best performance			
		Skylark	S-10P	1000W		Not recommended			

^{*}Low end of this range is determined by output current which may not directly translate to the perceived light output

WAC Lighting fixtures are compatible with a variety of dimmers. For your convenience we have included a compatibility chart showing dimmers which have been tested with our products. The recommended list below is based upon testing conducted in a lab, and the results can vary in certain field applications due to a number of factors. Exclusion from the list does not imply incompatibility, just that it has not been tested by WAC Lighting. Please reference the dimmer manufacturer's instructions for installation, or contact a WAC lighting professional at 800-526-2588.

Spacing Recommendations for Optimal Light Distribution


Corridors / Hallways



Stairs - Wall Mount



Stairs - Step Mount



Mount in center of stair as close to the upper tread as possible. For best results use one light per step for steps narrower than 5 feet

