Fixture Type:

Catalog Number:

Project:

Location:

Endurance[™] Brick Lights

Opal Step And Wall Light

Model & Voltage	Color Temp & CRI	Lumens	Finish
WL-5105 120 VAC	3000K 90	110	ABK Architectural Black ABZ Architectural Bronze AGH Architectural Graphite AWT Architectural White

Example: WL-5105-30-ABK

DESCRIPTION

Designed for integration into brick walls or vertical risers. The energyefficient Endurance LED Brick Light features a die-cast aluminum housing and integrated LED light engine with a heat resistant opal glass diffuser for a glare-free even spread of light, making outdoor areas safer and more secure.

FEATURES

- Frosted tempered glass lens for even illumination
- Factory sealed LED light engine
- 5 year warranty

SPECIFICATIONS

Construction:	Die-cast aluminum (K-Alloy)			
Power:	5.5W			
Input:	120 VAC, 50/60Hz			
Dimming:	ELV: 100-10%			
Light Source:	Integrated LED			
Rated Life:	80000 Hours			
Mounting:	Mortar into masonry, screw into wood walls, or retrofit into existing brick light installations, Can be mounted on wall vertically or horizontally			
Cut Out:	3 1/4" x 8"			
Finish:	Electrostatically Powder Coated Architectural White, Architectural Graphite, Architectural Bronze, Architectural Black			
Operating Temp:	-40°F to 122°F (-40°C to 50°C)			
Standards:	ETL, cETL, Wet Location Listed, IP66, ADA			


REPLACEMENT PARTS

5105-COV-AWT - Opal Cover Plate AWT 5005-30 - Brick Light Engine 3000K 5005-PLATE - Mnt Plate for Light Engine 5105-COV-AGH - Opal Cover Plate AGH 5105-COV-ABZ - Opal Cover Plate ABZ 5105-COV-ABK - Opal Cover Plate ABK



FINISHES

Architectural Black	Architectural Bronze	Architectural Graphite	Architectura White
LINE DRA	WING		





1509 S. La Cienega Blvd. Los Angeles, CA 90035 T: 310. 826. 7777 info@liteninc.com

