
LANDSCAPE LIGHTING





SPECIFICATIONS

Fixture Type:

Project:

Location:

Catalog Number:

Input: 9 -15VAC

 Power:
 1W to 7W / 2VA -10.5VA

 Brightness:
 45 lm to 365 lm

 Beam Angle:
 10° to 50°

 CRI:
 85

 Rated Life:
 70,000 hours

PRODUCT DESCRIPTION

Landscape mini accent luminaire. One fixture replaces all older halogen landscape accent lights

FEATURES

- \bullet Continuously Adjustable Beam Angles. Indexed at $10^{\it o}$, $25^{\rm o}$, $40^{\rm o}$, $50^{\rm o}$
- Continuously Adjustable brightness control. Indexed at 1W, 2W, 4W, 6W, 7W
- IP66 rated, Protected against high-pressure water jets
- Solid diecast brass or corrosion resistant aluminum
- Factory sealed water tight fixtures
- Constant output for 9V-15V input
- Can be used as an uplight or downlight
- 2700K or 3000K color temperature
- Mounting stake, detachable shroud, 6' lead wire and direct burial gel filled wire nuts included

ORDERING NUMBER

	Color	Temp	Finish	
5111 Mini Accent 12V	27 30	2700K Warm White 3000K Pure White	BK BZ BBR	Black on Aluminum Bronze on Aluminum Bronze on Brass

5111-30

Example: 5111-30BBR

MINI ACCENT 12V

5111

LANDSCAPE LIGHTING

Accessories						
Accent Snoot	5111-SNOOT-BK 5111-SNOOT-BZ 5111-SNOOT-BBR		Black on Aluminum Bronze on Aluminum Bronze on Brass		Shields lamp and reduces glare	
5" Long Shroud	5111-LSHR-BK 5111-LSHR-BZ 5111-LSHR-BBR		Black on Aluminum Bronze on Aluminum Bronze on Brass		Reduce glare. Ideal for downlighting application	
Additional Stake	9000-ST9-BZ		Bronze		Durable PVC stake	
Surface Mount Flange/Stake	5000-SCP-BZ 5000-SCP-BBR 5000-SCP-BK		Bronze on Aluminum Bronze on Brass Black on Aluminum		Includes three 7 inch threaded stainless steel stabilizing pins for ground mounting or surface mounts with four screws or over a junction box	
Guardian Mount	9000-SP9-BZ		Stainless Steel		Heavy duty stainless steel spike to position fixture Formed from a single piece of metal	
Gutter Mount Bracket	5000-GM-BZ 5000-GM-Bk		Stainless Steel		Stainless Steel universal mounting bracket for gutter mounting fixture	
Tree Mount Junction Box	5000-TCP-BZ 5000-TCP-BK		Bronze on Aluminum Black on Aluminum		Bronze on Aluminum box with Stainless steel mounting screws. Two ½" NPT threaded holes	
Optics	LENS-16-AMB LENS-16-GRN LENS-16-RED LENS-16-BLU	Amber Green Red Blue	LENS-16-FR LENS-16-SPR LENS-16-BEL	Frosted Spread Elongating	Enhances saturation of florals and foliage	
Extension Rods	5000-X04-BZ 5000-X04-BK 5000-X08-BZ 5000-X08-BK 5000-X12-BZ 5000-X12-BK	4 in 4 in 8 in 8 in 12 in	5000-X18-BZ 5000-X18-BK 5000-X24-BZ 5000-X24-BK	18 in 18 in 24 in 24 in	Extends distance between Accent light and Surface Mount Canopy, Stake, or Tree Mount box	
Rod L-Coupler	5000-LCO-BZ		Bronze			

Magnetic Transformers

Stainless Steel, 12-15V output, IP65 rated, UL 1838 listed See transformer spec sheet for details and its accessories

9075-TRN-SS 75W Max

9150-TRN-SS *150W Max*

9300-TRN-SS 300W Max

9600-TRN-SS 600W Max



