

2036R Compact Utility Tractor (EU Spec)



The 2R Series Tractors are designed for operators who demand the best available performance, yet desire a relatively compact machine. With engine power of 27.3 kW (36.6 hp), the 2036R will exceed operator expectations for power across the expanse of Category 1 implements mounted in the rear and/or front of the tractor.

The 2036R features a standard two-range hydrostatic transmission, 4-wheel drive (4WD) and power steering.

This tractor is primed for any property maintenance job. The industry-exclusive AutoConnect™ mower decks with CommandCut™ height-of-cut control, Quik-Park™ loaders, and A-frame 3-point front hitch come on and off so easily that operators can rapidly switch tasks in no time. Operators with substantial grass mowing jobs will be attracted to the range of implements and the ease of attachability that the 2036R provides.

Note: Pre-production model shown, some attachments/accessories may not be available.

Specifications

| Model | 2036R |
|-------------------------|--|
| Engine | Yanmar® 3-cylinder diesel iT4 |
| Power | 27.3 kW (36.6 hp), ECE-R120 net bare engine power @ rated engine RPM |
| Displacement | 1.496 L (91.3 cu in.) |
| Aspiration | Turbocharged |
| Cooling | Liquid |
| Lubrication | Pressurised |
| Engine Torque | Max. torque 120 Nm (88.5 lb-ft.), @ rated speed 103 Nm (76 lb-ft.) |
| Fuel System Type | Direct Injection |
| Fuel Tank Capacity | 32 L |
| Alternator (12-V) | 85 amp |
| Battery Size | 500 CCA |
| Transmission | Hydrostatic |
| Steering | Power steering |
| Axle Capacity | Front: 880 kg / Rear: 1,800 kg |
| Hydraulic Type | Open centre |
| Hydraulic Output | 35.2 Lpm |
| Max. Operating Pressure | 172.4 bar (2,500 psi) |
| PTO Drive | Rear: 540 RPM / Mid: 2,000 RPM |
| Brakes | Wet disc |
| 3-Point Hitch | Category 1,615 kg (1,365 lb.) lift capacity |
| Mower Decks | 60D or 72D AutoConnect™ Mid-Mount |
| Loader | 220R |
| Backhoe | 270B |
| Wheelbase Dimension | 172.5 cm (67.9 in.) |
| Turning Radius | 2.75 m (9 ft.), without brakes 2.6 m (8.5 ft.) |
| Shipping Weight | 1,105 kg |
| Tyres | Front: 23x8.50-14 / Rear: 14-17.5 |



Note: Pre-production model shown, some attachments/accessories may not be available.

This literature has been compiled for worldwide circulation. While general information, pictures, and descriptions are provided, some illustrations and text may include finance, credit, insurance, product options and accessories NOT AVAILABLE in all regions, and in some countries products and accessories may require modifications or additions to ensure compliance with the local regulations of those countries. PLEASE CONTACT YOUR LOCAL DEALER FOR DETAILS. John Deere reserves the right to change specification and design of products described in this literature without notice. John Deere's green and yellow colour scheme, the leaping deer symbol and JOHN DEERE are trademarks of Deere & Company. All photography and illustrations contained herein are copyrighted assets of Deere & Company.

JohnDeere.com.au | JohnDeere.co.nz