

AP7820B



Metered rack Power Distribution Units (PDUs) provide real-time remote monitoring of connected loads. User-defined alarms warn of potential circuit overloads before ...

Includes: Cord Retention Bracket(s), Installation Guide, Rack Mounting Brackets, User Manual



Technical Specifications

Output

Nominal Output Voltage	208V, 230V
Overload Protection	No
Maximum Total Current Draw	10
Output Connections	(8) IEC 320 C13 (Battery Backup)
Different voltages and corresponding amperages	10A @ 230V, 12A @ 208VA

Input

Nominal Input Voltage	200V, 208V, 230V
Input frequency	50/60 Hz
Input Connections	IEC-320 C14
Cord Length	1.98meters
Load Capacity	2300VA
Maximum Input Current	15A
Regulatory Derated Input Current (North America)	10A

Physical

Maximum Height	44MM, 4.4CM
Maximum Width	444MM, 44.4CM
Maximum Depth	102MM, 10.2CM
Rack Height	1U
Net Weight	1.73KG
Shipping weight	2.91KG
Shipping Height	64MM, 6.4CM
Shipping Width	470MM, 47.0CM

Shipping Depth	337MM, 33.7CM
Environmental	
Operating Temperature	-5 - 45 °C
Operating Relative Humidity	5 - 95 %
Operating Elevation	0-3000meters
Storage Temperature	-25 - 65 °C
Storage Relative Humidity	5 - 95 %
Storage Elevation	0-15000meters
Conformance	
Approvals	cUL Listed, C-tick, CE, CSA, FCC Part 15 Class A, GOST, UL 60950, UL Listed, VDE, VCCI
Standard warranty	2 years repair or replace
Sustainable Offer Status	
RoHS	Compliant
REACH	REACH: Contains No SVHCs
Battery Directive	Compliant
Proposition 65 Warning	Available in Documentation tab