

OLEVEON FIT. SIMPLY PLANNED.
FLEXIBLY REFURBISHED.
FIT FOR THE FUTURE.

- Ideal refurbishment solution for simple 1:1 replacements due to extensive portfolio including DALI, sensor and WiFi options
- High-quality light and low operating costs thanks to 3D prismatic technology and energy efficiency of up to 145 lm/W
- Wide range of variants for customised lighting concepts
- Future-proof due to intelligent connectivity features and LiveLink connection
- Further customising during installation via multilumen variants

www.trilux.com/oleveon-fit-led

Detailed product information:
www.trilux.com/oleveon-fit-led

Oleveon Fit

Mounting type
Suspended
Surface-mounted

Mounting location
Wall
Ceiling
Outdoor wall, canopied
Outdoor ceiling

Beam characteristic
wide
lambertian

Luminaire luminous flux
1,750 - 7,900 lm

Colour rendering index | Light colour
Ra > 80
4,000 K
6,500 K

Service life
L80 = 50,000 h

Luminaire colour
light grey
transparent green

Operating mode
switchable and DALI dimmable (ETDD)
switchable (ET)

Connectivity
LiveLink integrated
Monitoring Ready
CLO ready
LiveLink WiFi

Additional equipment
HCL optional
Motion sensor
Through-wiring
Single battery system, 3 hours
Multilumen option
ADELS quick-connect system

Accessories
Theft protection
Sensor remote control
Steel strip suspensions
Wall holder
Through-wiring
Replacement diffusers

IP66

OLEVEON FIT

LUMINAIRES WITH HIGHER PROTECTION RATING



