



SCAN HERE FOR MORE INFORMATION AND/ OR SEE PAGE 96 FOR RELATED SYSTEM ATTACHMENTS

IMPACT WRENCHES

See index pages 138 - 139



	M12 FRAIWF12	M12 FRAIWF38	M18 BRAIW	M12 FSCIWF14	M12 FSCIWF38	M12 FCIWF38G3		M12 FCIWP12G3	M12 FCIWF12G3	M18 FIW2F38	M18 FIW2P12	M18 FIW2F12	M18 ONEIWF12	M18 FMTIW2F38
Platform	M12 FUEL™	M12 FUEL™	M18™	M12 FUEL™	M12 FUEL™	M12 FUEL™		M12 FUEL™	M12 FUEL™	M18 FUEL™	M18 FUEL™	M18 FUEL™	M18 FUEL™	M18 FUEL™
ONE-KEY™	-	-	-	-	-	-		-	-	-	-	-	ONE-KEY™	-
Tool reception	½" square	¾" square	¾" square	¼" square	¾" square	¾" square		½" square	½" square	¾" square	½" square	½" square	½" square	¾" square
Fastening torque (Nm)	270	270	40/ 76	41/ 68/ 95/ 9	68/ 203/ 271/ 14	271/ 406/ 542/ 20		271/ 406/ 542/ 20	271/ 406/ 542/ 20	102/ 203/ 339/ 34	102/ 203/ 339/ 34	102/ 203/ 339/ 34	40/ 120/ 220/ 300	475/ 610/ 745/ 47
Nut-busting torque (Nm)	300	300	-	136	305	745		745	745	339	339	339	300	813
Impact rate (ipm)	0-1,350/ 0-2,700/ 0-3,600	0-1,350/ 0-2,700/ 0-3,600	0 - 2,400 / 0 - 3,400	0-1,350 / 0-3,700 / 0-4,400 / 0-4,400	0-1,000 / 0-3,400 / 0-3,600 / 0-3,600	0-1,500 / 0-3,000 / 0-3,300 / -		0-1,500 / 0-3,000 / 0-3,300 / -	0-1,500 / 0-3,000 / 0-3,300 / -	0-1,000/ 0-2,400/ 0-3,500	0-1,000 / 0-2,400 / 0-3,500	0-1,000 / 0-2,400 / 0-3,400	1,300/2,100/2,550/3,200	0-900/ 0-2,100/ 0-3,100
Weight with battery pack (EPTA) (kg)	1.7 (M12 B4)	1.7 (M12 B4)	1.8 (M18 B5)	0.86 (M12 HB2.5)	0.91 (M12 HB2.5)	1.5 (M12 HB5)		1.5 (M12 HB5)	1.5 (M12 HB5)	1.8 (M18 B5)	1.8 (M18 B5)	1.8 (M18 B5)	1.8 (M18 B5)	2.3 (M18 B5)
Available versions														
-0	✓	✓	✓	✓	✓	✓		✓	✓	✗	✗	✗	✗	✗
-0X	✗	✗	✗	✗	✗	✗		✗	✗	✓	✓	✓	✓	✓
-252X	✗	✗	✗	✓	✓	✗		✗	✗	✗	✗	✗	✗	✗
-502X	✗	✗	✗	✗	✗	✓		✗	✓	✗	✓	✓	✓	✗



	M18 FMTIW2P12	M18 FMTIW2F12	M18 ONEFHIWP12	M18 ONEFHIWF12	M18 FHIW2F12	M18 FHIW2P12		M18 ONEFHIWF34	M18 ONEFHIWF1	M18 ONEFHIWF1DS	M18 ONEFHIWF1D	M18 ONEFHIWH716	M18 ONEFHIWF12E	M18 FHIWF1R
Platform	M18 FUEL™	M18 FUEL™	M18 FUEL™	M18 FUEL™	M18 FUEL™	M18 FUEL™		M18 FUEL™	M18 FUEL™	M18 FUEL™	M18 FUEL™	M18 FUEL™	M18 FUEL™	M18 FUEL™
ONE-KEY™	-	-	ONE-KEY™	ONE-KEY™	-	-		ONE-KEY™	ONE-KEY™	ONE-KEY™	ONE-KEY™	ONE-KEY™	ONE-KEY™	-
Tool reception	½" square	½" square	½" square	½" square	½" square	½" square		¾" square	1" square	1" square	1" square	7/16" Hex	½" square	1" square
Fastening torque (Nm)	475/ 610/ 745/ 47	475/ 610/ 745/ 47	190/ 400/ 1,017/ 1,017	130/ 400/ 1,356/ 1,356	881/ 1,220/ 1,491/ 68	475/ 1,017/ 1,220/ 68		702/ 1,138/ 1,627/ 1,627	530/ 1,020/ 1,800/ 2,033	1,180/ 1,254/ 1,966/ 2,576	1,180/ 1,254/ 1,966/ 2,576	1,017	102/ 203/ 610/ 1,017	730/ 1,500/ 2,000
Nut-busting torque (Nm)	881	881	1,491	1,898	2,034	1,491		2,034	2,400	2,711	2,711	1,017	1,500	2,000
Impact rate (ipm)	0-900 / 0-2,100 / 0-3,100	0-900 / 0-2,100 / 0-3,100	0-1,150/0-2,100/0-2,400/0-2,400	0-950/ 0-1,750/ 0-2,100/ 0-2,100	0-1,300/ 0-2,200/ 0-2,400/ 0-2,400	0-1,400/ 0-2,500/ 0-2,700/ 0-2,700		0-850/ 0-1,850/ 0-2,400/ 0-2,400	1,350/ 1,650/ 2,100/ 0-2,500	750/ 930/ 1,200/ 1,440	750/ 930/ 1,200/ 1,440	0- 800/ 0-1,300/ 0-2,600/ 0-1,600/ 0-2,400/ 0-2,400/ 0-2,400	1,750/ 2,150/ 2,500/ 2,500	
Weight with battery pack (EPTA) (kg)	2.3 (M18 B5)	2.3 (M18 B5)	3.2 (M18 B5)	3.3 (M18 B5)	3.4 (M18 B5)	3.4 (M18 B5)		3.5 (M18 B5)	5.9 (M18 FB8)	11.1 (M18 FB12)	12.7 (M18 FB12)	3.3 (M18 B5)	3.3 (M18 B5)	7.8 (M18 FB12)
Available versions														
-0C	✗	✗	✗	✗	✗	✗		✗	✗	✓	✓	✗	✗	✓
-0X	✓	✓	✓	✓	✓	✓		✓	✓	✗	✗	✓	✓	✗
-502X	✓	✓	✓	✓	✓	✓		✓	✗	✗	✗	✗	✗	✗
-802X	✗	✗	✗	✗	✗	✗		✗	✓	✗	✗	✗	✗	✗
-121C	✗	✗	✗	✗	✗	✗		✗	✗	✓	✓	✗	✗	✗
-122C	✗	✗	✗	✗	✗	✗		✗	✗	✗	✗	✗	✗	✓