ANGLE GRINDERS

SCAN HERE FOR MORE INFORMATION AND/ OR SEE PAGE 100 FOR RELATED SYSTEM ATTACHMENTS

See index pages 124 - 126













	M18 ONEFLAG230XPDB	M18 FLAG230XPDB	M18 FHSAG0180VXPDB2	M18 FHSAG150XPDB2	M18 FHSAG150XB2		M18 FHSAG125XPDB2	M18 FHSAG125XB2	M18 FHSAGSVO125X	M18 FSAGSVO125X	M18 FHSAG0125VXPDB2	M18 ONEFSAG125XPDB
Platform	M18 FUEL™	M18 FUEL™	M18 FUEL™	M18 FUEL™	M18 FUEL™		M18 FUEL™	M18 FUEL™	M18 FUEL™	M18 FUEL™	M18 FUEL™	M18 FUEL™
Feature	RAPIDSTOP™	-	RAPIDSTOP™	RAPIDSTOP™	RAPIDSTOP™		RAPIDSTOP™	RAPIDSTOP™	RAPIDSTOP™	RAPIDSTOP™	RAPIDSTOP™	RAPIDSTOP™
ONE-KEY™	ONE-KEY™	-	ONE-KEY™	-	-		-	-	ONE-KEY™	ONE-KEY™	ONE-KEY™	ONE-KEY™
No load speed (rpm)	6,600	6,600	5,000 - 8,400	9,000	9,000		9,000	9,000	3,000 - 9,000	3,500 - 8,500	3,500 - 9,000	8,500
Disc diameter (mm)	230	230	180	150	150		125	125	125	125	125	125
Weight with battery pack (EPTA) (kg)	5.4 (M18 HB12)	5.3 (M18 HB12)	3.6 (M18 FB8)	3.5 (M18 FB8)	3.5 (M18 FB8)		3.5 (M18 FB8)	3.5 (M18 FB8)	3.7 (M18 FB8)	3.0 (M18 B5)	3.5 (M18 FB8)	2.7 (M18 B5)
Switch type	Paddle (Deadman) switch	Paddle (Deadman) switch	Paddle (Deadman) switch	Paddle (Deadman) switch	Slide lock-on switch		Paddle (Deadman) switch	Slide lock-on switch	Deadman switch	Deadman switch	Paddle (Deadman) switch	Paddle (Deadman) switch
Brake	Yes	Yes	Yes	Yes	Yes		Yes	Yes	Yes	Yes	Yes	Yes
Anti-kickback protection	Yes	Yes	Yes	Yes	Yes		Yes	Yes	Yes	Yes	Yes	Yes
FIXTEC™	Yes	Yes	Yes	Yes	Yes		Yes	Yes	Yes	Yes	Yes	Yes
Line lock out function	Yes	Yes	Yes	Yes	Yes		Yes	Yes	Yes	Yes	Yes	Yes
Available versions												
-0	✔	✘	✘	✘	✘		✘	✘	✘	✘	✘	✘
-0C	✔	✔	✘	✘	✘		✘	✘	✘	✘	✘	✘
-0X	✘	✘	✔	✔	✔		✔	✔	✔	✔	✔	✔
-502X	✘	✘	✘	✘	✘		✘	✘	✘	✔	✘	✔
-802X	✘	✘	✘	✘	✘		✔	✔	✘	✘	✔	✘
-121C	✘	✔	✘	✘	✘		✘	✘	✘	✘	✘	✘
-122C	✔	✘	✘	✘	✘		✘	✘	✘	✘	✘	✘













	M18 ONEFSAG125XB	M18 FSAG125XB	M18 FSAG125X	M18 FSAGV125XPDB	M18 FSAGV125XB		M18 FSAGF125XPDB	M18 FSAGF125XB	M18 BLSAG125X	M18 BLSAG125XPD	M18 BLSAG115XPD	M12 FCOT
Platform	M18 FUEL™	M18 FUEL™	M18 FUEL™	M18 FUEL™	M18 FUEL™		M18 FUEL™	M18 FUEL™	M18™	M18™	M18™	M12 FUEL™
Technology	-	-	-	-	-		-	-	Brushless	Brushless	Brushless	-
Feature	RAPIDSTOP™	RAPIDSTOP™	-	RAPIDSTOP™	RAPIDSTOP™		RAPIDSTOP™	RAPIDSTOP™	-	-	-	-
ONE-KEY™	ONE-KEY™	-	-	-	-		-	-	-	-	-	-
No load speed (rpm)	8,500	8,500	8,500	3,500 - 8,500	3,500 - 8,500		8,500	8,500	11,000	11,000	11,000	20,000
Disc diameter (mm)	125	125	125	125	125		125	125	125	125	115	76
Weight with battery pack (EPTA) (kg)	2.7 (M18 B5)	2.7 (M18 B5)	2.7 (M18 B5)	2.7 (M18 B5)	2.7 (M18 B5)		2.6 (M18 B5)	2.6 (M18 B5)	2.4 (M18 B4)	2.4 (M18 B4)	2.4 (M18 B4)	1.1 (M12 B2)
Switch type	Slide lock-on switch	Slide lock-on switch	Slide lock-on switch	Paddle (Deadman) switch	Slide lock-on switch		Paddle (Deadman) switch	Slide lock-on switch	Slide lock-on switch	Paddle (Deadman) switch	Paddle (Deadman) switch	Trigger lock-off switch
Brake	Yes	Yes	No	Yes	Yes		Yes	Yes	No	No	No	No
Anti-kickback protection	Yes	Yes	Yes	Yes	Yes		Yes	Yes	Yes	Yes	Yes	No
FIXTEC™	Yes	Yes	Yes	Yes	Yes		Yes	Yes	Yes	Yes	Yes	No
Line lock out function	Yes	Yes	Yes	Yes	Yes		Yes	Yes	Yes	Yes	Yes	Yes
Available versions												
-0	✘	✔	✔	✘	✔		✘	✘	✔	✔	✔	✔
-0X	✔	✔	✔	✔	✔		✔	✔	✘	✘	✘	✘
-402X	✘	✘	✘	✘	✘		✘	✘	✔	✔	✘	✘
-422X	✘	✘	✘	✘	✘		✘	✘	✘	✘	✘	✔
-502X	✘	✔	✘	✘	✘		✘	✘	✘	✘	✘	✘

For further technical specifications, including noise and vibration data, please visit our website: www.milwaukeetool.eu