MONTY®



monty®

TYRE CHANGERS

OPTIONAL EXTRAS

	26582	Plastic protector for bead breaker blade
	4026853	Plastic rim protector set (option for monty® 1270 smart, 3300-20 smart, standard on all other tyre changers)
	4024784 4027646 4029337	Plastic mounting head Plastic mounting head for rims with elevated spokes Mounting head for motorcycle wheels (not for monty® 3550 series)
	4028229	Quick exchange device including plastic mounting head for rims with elevated spokes
	4028629	+4" quick-exchange device including steel mounting head for monty® racing smartSpeed/GP and monty® 3300-24 smartSpeed/GP
	4029455	+4" adaptors to increase outer clamping range for monty® 3300 racing smartSpeed/GP and monty® 3300-24 smartSpeed/GP
	4030649	+6" adaptors to increase outer clamping range for monty® 1270 smart, 3300-20 smart/GP and 3300-22 smartSpeed/GP
	4027629	Light-truck adaptors 17,5" for monty® 3300 racing smartSpeed/GP and monty® 3300-24 smartSpeed/GP
	4030651	Light-truck adaptors 17,5" for monty® 1270 smart, 3300-20 smart/GP and 3300-22 smartSpeed/GP
	4028568	Motorcycle adaptors for monty® racing smartSpeed/GP and monty® 3300-24 smartSpeed/GP
	4030648	Motorcycle adaptors for monty® 1270 smart, 3300-20 smart/GP and 300-22 smartSpeed/GP
	4026290	Roller board for monty® 1270 smart up to monty® 3300 racing smartSpeed
	EAK-0279G89A EAK-0279G86A EAK-0279G87A	CW1015 wheel lift for monty® 3300-20 smart, 3300-22 smartSpeed, 3300-24 smartSpeed CW1025 wheel lift for monty® 3300 racing smartSpeed Wheel lift for monty® 3550

TECHNICAL DATA

monty®		1270 smart	3300-20 smart plus/GP	3300-22 smartSpeed/GP plus	3300-24 smartSpeed/GP plus	3300 racing smartSpeed/GP plus	3550
Inner clamping range	inch	12 – 22	12 – 22	12 – 24	12 – 24	12 – 24	14 – 26
Outer clamping range	inch	10 – 20	10 – 20	10 – 22	10 – 24	10 – 24	12 – 26
Rim width	inch	3 – 11	3 – 12	3 – 12	3 – 12	3 – 14	3 – 16
Max. tyre width	inch	12	13	13	13	15	17
Max. wheel diameter	mm	1000	1000	1000	1000	1000	1200
Speed	rpm	7	7	7 / 7 – 18	7 / 7 – 18	7 / 7 – 18	7/7 – 20
Bead breaking range	mm	70 – 340	70 – 340	40 – 392	40 – 392	40 – 392	70 – 410
Compressed air supply	bar	8 – 12	8 – 12	8 – 12	8 – 12	8 – 12	8 – 12
Dimensions (W x D x H)	mm	1150x1030x1730	1160x1700x1850	1300x1700x1860	1220x1700x1870	1350x1800x1920	1850x1960x2270
Weight	kg	173	300	300	310	315	485
Power supply		400 V 3ph 50 Hz	400 V 3ph 50 Hz	230 V 1ph 50–60 Hz	230 V 1ph 50–60 Hz	230 V 1ph 50–60 Hz	230 V 1ph 50–60 Hz

EMEA-JA
Snap-on Equipment s.r.l. · Via Prov. Carpi, 33 · 42015 Correggio (RE)
Phone: +39 0522 733-411 · Fax: +39 0522 733-479 · www.hofmann-equipment.com

Austria
Snap-on Equipment Austria GmbH · Hauptstrasse 24/Top 14 · A-2880 St. Corona/Wechsel (RE)
Phone: +43 1 865 97 84 · Fax: +43 1 865 97 84 29 · www.hofmann-equipment.com

France
Snap-on Equipment France · ZA du Vert Galant · 15, rue de la Guivernone BP 97175
Saint-Ouen-l'Aumône · 95056 Cergy-Pontoise CEDEX
Phone: +33 134 48 58-78 · Fax: +33 134 48 58-70 · www.hofmann-equipment.com

Germany
Snap-on Equipment GmbH · Konrad-Zuse-Straße 1 · 84579 Unterneukirchen
Phone: +49 8634 622-0 · Fax: +49 8634 5501 · www.hofmann-equipment.com

Italy
Snap-on Equipment s.r.l. · Via Prov. Carpi, 33 · 42015 Correggio (RE)
Phone: +39 0522 733-411 · Fax: +39 0522 733-410 · www.hofmann-equipment.com

United Kingdom
Snap-on Equipment Ltd. · Unit 17 Denney Road, King's Lynn · Norfolk PE30 4HG
Phone: +44 118 929-6811 · Fax: +44 118 966-4369 · www.hofmann-equipment.com

Part of the machines is illustrated with optional extras which are available at extra cost. Technical and visual modifications reserved.

Cod.: 9702 170 · 05/2021

HOFMANN®