



• For Touch Up Use Only Directions for use:

- 1. Clean surface to be sprayed.
- 2. For best results, can should be at room temperature.
- 3. Shake can for one minute after mixing balls rattle.
- 4. Apply in several thin, even coats.
- 5. For best results do not apply in conditions of high heat and humdity.
- To prevent clogging and to clear spray tip after each use, turn can upside down and spray until only clear gas is emitted.
- 7. UNDER NO CIRCUMSTANCES STICK ANY SHARP OBJECT INTO THE HOLE ON THE TOP OF THE METAL CAN.

Munsell Green Spray Paint sold in 12 oz. cans.

ORDIC FIBERGLASS, INC.

Quality Fiberglass Products for the Electrical Industry

P.O. Box 27 • Warren, Minnesota 56762 • Phone: 218-745-5095 • Fax: 218-745-4990 • nordicfiberglass.com

MUNSELL GREEN

READY

EXTREMELY FLAMMABLE LIQUID AND VI VAPORS MAY CAUSE FLASH VAPORS MAY CAUSE FLASH CONTENTS UNDER PRES CONTENTS UNDER PRES CAUSING DIZZINESS, HEADACHE OR WITH CAUSING DIZZINESS, HEADACHE OR WITH CAUSING DIZZINESS, HEADACHE OR WITH