

CARD AUTHENTICATION SOLUTION

HIGHLIGHTS

Improved device-level security

Seamless integration with your business infrastructure using most common company ID badges

Print directly from your network and securely retrieve your documents

Restrict, limit and authorize device access by user or department

Track usage for reporting and accounting purposes

Choose from local or network authentication for varying levels of security features and tracking capabilities

Advanced functionality available with Kyocera HyPAS business applications and integrated MFP security features

ONE SWIPE DOES IT ALL: AUTHORIZE, RESTRICT, LIMIT

Protecting information is essential to your business. The Kyocera Card Authentication Solution is a quick and convenient security option for your multifunctional devices utilizing employee ID badges. With a simple swipe of a badge, users gain immediate access to their Kyocera MFP, authorizing them to use features specific to their job function. With the Card Authentication Solution installed, corporate network resources and information can be secured, preventing unauthorized access.

The Kyocera Card Authentication Solution also enables administrators to track usage for reporting or accounting purposes, therefore saving your organization unnecessary waste. By leveraging select Kyocera MFPs, your business is able to protect vital information without the need to invest in additional security cards and high-priced hardware. The Kyocera Card Authentication Solution is a cost-effective solution for any enterprise.

HOW IT WORKS:

The Card Authentication Solution includes administrative software from Kyocera and a card reader from RF IDEas, which quickly and easily connects into your Kyocera MFP's USB port. Once installed and configured, users simply swipe their badges at the card reader. They are quickly authenticated and logged onto the device, allowing instant access to the MFP and secure retrieval of printed documents. It's that simple!





CARD AUTHENTICATION SOLUTION

FEATURES

The Card Authentication Solution includes Kyocera software and a card reader by RF IDEas, all of the items necessary to connect to select Kyocera MFPs.

Easy Interface

The plug-n-play reader design is truly easy to integrate into select Kyocera MFPs. The pcProx or AIR ID Card Reader connects directly to the USB port for advanced security. Ethernet reader connectivity option available on select Kyocera MFPs.

Available Card Readers

- Air ID Enroll Mifare
- HID Prox
- HID iClass
- HID Prox Indala

Compatibility

Card Authentication Solution is compatible with:

- TASKalfa/CS 7550ci/6550ci/5550ci/4550ci/3550ci/3050ci/255c/205c; FS-C2626MFP/FS-C2526MFP and FS-C2126MFP+ Color MFPs
- TASKalfa/CS 8000i/6500i/5500i/4500i/3500i/305/255; FS-3640MFP/FS-3540MFP and FS-3140MFP+ Black and White MFPs
- Legacy TASKalfa and CS MFPs*

*For a complete list of compatible MFPs please visit www.kyoceramita.com or www.copystar.com.

Improves Accuracy of Information & Productivity

- Choose the level of authentication and authorization that fits your organization's infrastructure
- Eliminates errors associated with manual entry of user credentials at the device
- Assists with select regulatory compliance requirements for device access and tracking

HyPAS™

Kyocera's HyPAS (Hybrid Platform for Advanced Solutions) is a powerful and scalable software solution platform. Through integration with widely accepted software applications, HyPAS will enhance your specific document imaging needs, resulting in improved information sharing, resource optimization and document workflows.

SPECIFICATIONS – Card Reader

Product name: Card Authentication Solution (B)

Typical maximum read range: 1.0" – 3.0" (2.5 – 7.6cm) dependent upon proximity card type and environmental conditions

Reader dimensions: 3 3/8" x 2" x 0.6"

Reader weight: 0.45 lbs (12.7g)

Power supply and interface: Self-powered 6' USB cable

Indicators: Tri-state LED, beeper

Transmit frequency: pc Prox: 125 kHz

AIR ID: 13.56 MHz

Operating temperature range: -22° to 150° F (-30° to 65° C)

Operating humidity range: 5% to 95% relative humidity, non-condensing

Storage temperature range: -40° to 185° F (-40° to 85° C)

Certifications: FCC, United States; CE Mark Europe,

C-TICK, RoHS, Industry Canada

Supported Cards – Partial List

pc Prox: HID Prox, Indala Prox

AIR ID: HID iClass

Enroll Mifare



Specifications and design are subject to change without notice. For the latest on connectivity visit www.kyoceramita.com. All trademarks are the property of their respective owners.

Kyocera Mita America, Inc. Headquarters: 225 Sand Road, Fairfield, NJ 07004-0008, USA
©2011 Kyocera Mita America, Inc.