

→ 5009 HIGH CAPACITY CROSS-CUT SHREDDER

extra-large feed table with conveyor belt and electronically secured safety guard | easy-to-use control panel with push buttons for forward, stop, and reverse | safety lock and key, main switch, and emergency stop button | automatic reverse and re-feed in case of paper jam | optical indicators show operational status | two automatic speed modes: "Power" for bulk feeding large quantities of paper, and "Speed" for high speed shredding of smaller amounts | high quality, hardened steel cutting shafts are soft metal resistant and can take CDs, VHS tapes, hardbound documents, and 3-ring binders | lifetime warranty on the cutting shafts | convenient, centralized oiler for lubrication of the cutting head | dual 3 phase motors (24 maximum horsepower) rated for continuous operation | durable gears enclosed in dust-proof housing | large shred compartment with easy-access door located at rear of machine | mobile shred cart with bag mounting frame for easy replacement of disposable shred bags | 79 gallon shred volume | automatic power cut-off when shred bag is full or when cabinet door is opened | thermal switch prevents overheating | mounted on heavy duty casters | optional accessories: modular conveyor belt system and additional shred carts

Dimensions (D x W x H): 85 ½ x 40 ¼ x 67 ½ inches (depth with conveyor system: 121 inches), Shipping weight: 3,080 lbs.





3134 Industry Drive North Charleston, South Carolina 29418 800-223-2508, fax: 843-552-2974 www.mbmcorp.com



1675 Sismet Road, unit 4 Mississauga, Ontario L4W 4K8 800-387-2528, fax: 905-840-1114 www.ideal-mbm.com

CENTRALIZED OILER



A centralized oiler provides quick and easy lubrication of the cutting head.

POWERFUL CUTTING HEAD



The high quality, tempered steel cutting head allows shredding of hardbound documents, including 3-ring binders.



The electronically secured door at rear of machine allows safe and easy removal of shred cart.

→ 5009 CROSS-CUT	
	1/32'' x 1 ½''–3'' (6 x 50 mm)
Sheet capacity	600+*
Security level	2
Feed opening	20''
Max. horsepower	24
* may vary due to variations in paper and power supply	

All technical data is approximate and subject to change. © MBM Corporation, 9/2009.