

## IDS-7200HQHI-K2/4S SERIES TURBO ACUSENSE DVR

### Key Features

- Support Deep learning-based analysis
- Support H.265 Pro+/H.265 Pro/H.265 video compression
- Support HDTV/AVHD/CVI/CVBS/IP video input
- Max. 12/24 IP cameras input (up to 6 MP)
- Max. 800 m for 1080p and 1200 m for 720p HDTV signal transmission
- Up to 10 TB capacity per HDD



### Compression and Recording

- H.265 Pro+ can be enabled to improve encoding efficiency and reduce data storage costs
- Full channel recording at up to 4 MP lite resolution

### Storage and Playback

- Two SATA interfaces
- Smart search for efficient playback
- Support the third party cloud storage (Dropbox/Google Drive/Microsoft OneDrive)

### Smart Function

- Support multiple VCA (Video Content Analytics) events for both analog and smart IP cameras
- Deep learning-based analysis: re-recognition of the human body or vehicle target in behavior detection to filter false alarm, support 4-ch detection

### Network & Ethernet Access

- Hik-Connect & DDNS (Dynamic Domain Name System) for easy network management
- Output bandwidth limit configurable




## Specifications

Model	iDS-7208HQHI-K2/4S	iDS-7216HQHI-K2/4S
<b>Recording</b>		
<b>Video compression</b>	H.265 Pro+/H.265 Pro/H.265/H.264+/H.264	
<b>Encoding resolution@ Frame rate</b>	Main stream: When 1080p Lite mode not enabled: For 4 MP stream access: 4 MP lite@15fps; 1080p lite/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N) For 3 MP stream access: 3 MP/1080p/720p/VGA/WD1/4CIF/CIF@15fps For 1080p stream access: 1080p/720p@15fps; VGA/WD1/4CIF/CIF@25fps (P)/30fps (N) For 720p stream access: 720p/VGA/WD1/4CIF/CIF@25fps (P)/30fps (N) When 1080p Lite mode enabled: 4 MP lite/3 MP@15fps; 1080p lite/720p lite/VGA/WD1/4CIF/CIF@25fps (P)/30fps (N) Sub-stream: WD1/4CIF@12fps; CIF@25fps (P)/30fps (N)	
<b>Video bit rate</b>	32 Kbps to 6 Mbps	
<b>Dual stream</b>	Support	
<b>Stream type</b>	Video, Video & Audio	
<b>Audio compression</b>	G.711u	
<b>Audio bit rate</b>	64 Kbps	
<b>Video and Audio</b>		
<b>IP video input</b>	4-ch (up to 12-ch)	8-ch (up to 24-ch)
	Up to 6 MP resolution	
	Support H.265+/H.265/H.264+/H.264 IP cameras	
<b>Analog video input</b>	8-ch	16-ch
	BNC interface (1.0 Vp-p, 75 Ω), supporting coaxitron connection	
<b>HDTV I input</b>	4 MP, 3 MP, 1080p30, 1080p25, 720p60, 720p50, 720p30, 720p25 *: The 3 MP signal input is only available for channel 1/2 of iDS-7208HQHI-K2/4S, and for channel 1/2/3/4 of iDS-7216HQHI-K2/4S.	
<b>AHD input</b>	4 MP, 1080p25, 1080p30, 720p25, 720p30	
<b>HDCVI input</b>	1080p25, 1080p30, 720p25, 720p30	
<b>CVBS input</b>	PAL/NTSC	
<b>CVBS output</b>	1-ch, BNC (1.0 Vp-p, 75 Ω), resolution: PAL: 704 × 576, NTSC: 704 × 480	
<b>HDMI/VGA output</b>	1-ch, 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz, HDMI/VGA Simultaneous Output	
<b>Audio input</b>	1-ch, RCA (2.0 Vp-p, 1 KΩ)	
<b>Audio output</b>	1-ch, RCA (Linear, 1 KΩ)	
<b>Two-way audio</b>	1-ch, RCA (2.0 Vp-p, 1 KΩ) (using the first audio input)	
<b>Synchronous playback</b>	8-ch	16-ch
<b>Network</b>		
<b>Remote connections</b>	64	128
<b>Network protocols</b>	TCP/IP, PPPoE, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, NFS, iSCSI, UPnP™,	

	HTTPS, ONVIF	
<b>Network interface</b>	1, RJ45 10M/100M self-adaptive Ethernet interface	1, RJ45 10M/100M/1000M self-adaptive Ethernet interface
<b>Auxiliary interface</b>		
<b>SATA</b>	2 SATA interfaces	
<b>Capacity</b>	Up to 10 TB capacity for each disk	
<b>Serial interface</b>	RS-485 (half-duplex)	
<b>USB interface</b>	2 × USB 2.0	
<b>Alarm in/out</b>	N/A	
<b>General</b>		
<b>Power supply</b>	12 VDC	
<b>Consumption (without HDD)</b>	≤ 18 W	≤ 25 W
<b>Working temperature</b>	-10 °C to +55 °C (+14 °F to +131 °F)	
<b>Working humidity</b>	10% to 90%	
<b>Dimensions (W × D × H)</b>	380 × 320 × 48 mm (15.0 × 12.6 × 1.9 inch)	
<b>Weights (without HDD)</b>	≤ 1.78 kg (3.9 lb)	≤ 2 kg (4.4 lb)

## Physical Interfaces



\*: The rear panel of iDS-7208HQHI-K2/4S provides 8 video input interfaces.

No.	Description	No.	Description
1	VIDEO IN	7	LAN Network Interface
2	AUDIO IN, RCA Connector	8	RS-485 Serial Interface
3	AUDIO OUT, RCA Connector	9	12 VDC Power Input
4	VGA Interface	10	Power Switch
5	HDMI Interface	11	GND
6	USB Interface	12	VIDEO OUT

## Available Models

iDS-7208HQHI-K2/4S, iDS-7216HQHI-K2/4S

Distributed by



### Headquarters

No.555 Qianmo Road, Binjiang District,  
Hangzhou 310051, China  
T +86-571-8807-5998  
overseasbusiness@hikvision.com

**Hikvision USA**  
T +1-909-895-0400  
sales.usa@hikvision.com

**Hikvision Australia**  
T +61-2-8599-4233  
salesau@hikvision.com

**Hikvision India**  
T +91-22-28469900  
sales@pramahikvision.com

**Hikvision Canada**  
T +1-866-200-6690  
sales.canada@hikvision.com

**Hikvision Thailand**  
T +662-275-9949  
sales.thailand@hikvision.com

**Hikvision Europe**  
T +31-23-5542770  
sales.eu@hikvision.com

**Hikvision Italy**  
T +39-0438-6902  
info.it@hikvision.com

**Hikvision Brazil**  
T +55 11 3318-0050  
Latam.support@hikvision.com

**Hikvision Turkey**  
T +90 (216)521 7070- 7074  
sales.tr@hikvision.com

**Hikvision Malaysia**  
T +601-7652-2413  
sales.my@hikvision.com

**Hikvision UK & Ireland**  
T +01628-902140  
sales.uk@hikvision.com

**Hikvision South Africa**  
Tel: +27 (10) 0351172  
sale.africa@hikvision.com

**Hikvision France**  
T +33(0)1-85-330-450  
info.fr@hikvision.com

**Hikvision Kazakhstan**  
T +7-727-9730667  
nikia.panfilov@hikvision.ru

**Hikvision Vietnam**  
T +84-974270888  
sales.vt@hikvision.com

**Hikvision UAE**  
T +971-4-4432090  
salesme@hikvision.com

**Hikvision Singapore**  
T +65-6684-4718  
sg@hikvision.com

**Hikvision Spain**  
T +34-91-737-16-55  
info.es@hikvision.com

**Hikvision Tashkent**  
T +99-87-1238-9438  
uzb@hikvision.ru

**Hikvision Hong Kong**  
T +852-2151-1761  
info.hk@hikvision.com

**Hikvision Russia**  
T +7-495-669-67-99  
saleru@hikvision.com

**Hikvision Korea**  
T +82-(0)31-731-8817  
sales.korea@hikvision.com

**Hikvision Poland**  
T +48-22-460-01-50  
info.pl@hikvision.com

**Hikvision Indonesia**  
T +62-21-2933759  
Sales.Indonesia@hikvision.com

**Hikvision Colombia**  
sales.colombia@hikvision.com