

JABRA EVOLVE 40

- Laptop and smart device connectivity
- Easy to use intelligent call transfer
- Integrated busy light


Jabra®

DETAIL	INFORMATION
Packaging dimensions	L 19.0 x W 25.5 x H 1.0 cm
Weight mono / duo	Mono headset 171.1 g Stereo headset 142.5 g
Whats in the box	Pouch, Evolve 40 Headset, Warning leaflet, Warranty leaflet, Quick Start Guide, Foam inlay (only available for duo), Layer card, Poly bag
Battery included	No
AC power supply	USB power supply by PC
Certifications	Regulatory Approvals: CE, FCC, KCC, RCM, UL Industrial Certifications: Lync, Avaya, Cisco, Alcatel Lucent and Astra
Bluetooth device	No
NFC	No
Headset bandwidth	Wideband
Connection (mini jack, USB, etc)	USB 2.0/3.0, 3.5mm jack
Speaker Size	D28x3.9mm
Speaker sensitivity	93.6dB SPL @1kHz
Speaker impedance	32+/-4.8Ω, @1.0kHz
Speaker Max Input Power	Rated Input 5mW @0.4V, max input 10mW @0.56V
Speaker Frequency Range	150Hz~7kHz, @Output S.P.L -10dB
Microphone type	Electret Condenser (ECM) Uni-Directional Microphone
Microphone Sensitivity	f=1kHz, Pin=1Pa,0dB=1V/Pa Min: -42 dB, Max: -38 dB
Microphone Frequency Range	100 Hz – 10 kHz
Speaker bandwidth Music mode	HiFi
Speaker bandwidth Speak mode	Wideband
Microphone bandwidth	Wideband
Cord length	Control cable: 95cm, HS cable: 120cm
Operating temperature	-10 °C to + 50 °C
Storage temperature	-30 °C to + 80 °C Storage temperature range: (-20°C to +35°C 6 months), (+35°C to +45°C 3 months), (+45°C to +45°C 1 month), (+60°C to +70°C 1 hour with no degradation), (+70°C to +85°C max. 1 hour (<20% degradation)
Power consumption speaker	Rated Input 5mW @0.4V, max input 10mW @0.56V
Features	Busy light, USB Controller, Discreet boom arm with magnet that integrates into the headset when not on calls, Connects to multiple devices (smartphone or tablet) with a 3.5mm jack

SKU	DESCRIPTION	EAN CODE
INSERT LOCAL SKU NUMBERS HERE		

* Phone dependent