



### PRODUCT DESCRIPTION

**Leak Repair Premium Liquid Rubber** is a unique rubber compound that is extremely effective for sealing fasteners, laps & penetrations on various roof surfaces. It is a one-component product that has excellent adhesion to properly prepared surfaces and is typically top-coated with RV2x RV Roof Coating.

**Leak Repair Premium Liquid Rubber** has excellent physical properties that is thermally stable and highly resistant to cracking and peeling due to ozone and ultraviolet exposure.

### TYPE OF APPLICATIONS:

- Fasteners, Flashings & Gutters
- Metal Buildings & Roofs
- Modified & BUR Roofs
- Polyurethane Foam & Concrete Surfaces or Roofs
- Single Ply Roofs
- Industrial Roofs

Leak Repair is a Miami-Dade County Product Control Approved. It is also approved by the State of Florida.

### SURFACE PREPARATION:

The surface must be free of any oils, moisture, rust scale, soil or other contaminants that may interfere with good adhesion. Remove any loose material from seams or other surfaces with a wire brush or scraper. Oil and grease should also be removed with solvents or an appropriate detergent cleaner. In many cases, high pressure water blast will be sufficient enough to prepare the surface.

### APPLICATION TEMPERATURES:

For best results, the temperature of the ambient air and the substrate should be within a range of 40° - 110°F. For best spray application, the product should be at a minimum of 70°F. Lower temperatures can be utilized for brush applications.

### APPLICATION METHODS:

Leak Repair Easy Squeeze Liquid Rubber can be applied by brush, rolled or pumped onto the surface. Apply heavy, uniform coats over fasteners & seams etc.

### Recommended Spray Equipment = Airless

TIP SIZE .....	0.025"
FLUID PRESSURE (PSI) .....	3000
FLUID HOSE SIZE .....	3/8" - 1/2"

### TECHNICAL DATA:

TYPE OF RESIN .....	SYNTHETIC RUBBER
COLOR .....	WHITE
ELONGATION .....	400%
TENSILE STRENGTH .....	1000 PSI
REDUCTION .....	NONE
FLASH POINT .....	101°F
SPECIFIC GRAVITY .....	0.94
WEIGHT (LB./GAL) .....	7.86
SOLIDS (%/WEIGHT) .....	60±1
SOLIDS (% BY VOL) .....	53±1
VISCOSITY* .....	12,000
VOC (GRAMS/LITER) .....	436
*CENTIPOISE @ 100°F	

### HANDLING & STORAGE:

Leak Repair Easy Squeeze Liquid Rubber contains a blend of solvents which is considered combustible by D.O.T. and O.S.H.A. standards. It should be used and stored away from flames in a well-ventilated atmosphere. Avoid prolonged breathing of vapors and prevent contact with eyes. Read all label information and precautions before using.

\*The specifications, properties and performance of materials described herein are based on information believed to be reliable. Unless otherwise expressly provided in written contract, the product discussed are sold without conditions or warranties, expressed or implied. Product specifications are subject to change without notice.