

SECTION 1 IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name : RV107x Rust Inhibitor

Product form : Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Corrosion Preventive Coating

1.3. Details of the supplier of the safety data sheet

Inland Coatings Holdings, LLC

26259 US-6

Adel, Iowa 50003

800-456-8467

1.4. Emergency telephone number

CHEMTREC : 800-424-9300

SECTION 2 HAZARDS IDENTIFICATION

Classification of the chemical in accordance with paragraph (d) of §1910.1200;

GHS Hazard Symbols



GHS Skin Corrosion/Irritation Category 2

CLASSIFICATION Serious Eye Damage/Eye Irritation Category 2B Flammable Liquid Category 3
Specific Target Organ Systemic Toxicity (STOT) - Single Exposure Category 3

SIGNAL WORD Warning

HAZARD STATEMENTS Flammable liquid and vapour. Causes skin and eye irritation May cause respiratory irritation.
May cause drowsiness or dizziness.
May cause cancer.

PRECAUTIONARY STATEMENTS

PREVENTION Keep away from heat/sparks/open flames/hot surfaces. – No smoking.
Ground/bond container and receiving equipment. Use explosion-proof equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge. Avoid breathing dust/fume/gas/mist/vapours/spray.
Wash thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Wear protective gloves/protective clothing/eye protection/face protection.

RESPONSE IF ON SKIN: Wash with plenty of soap and water.
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Call a POISON CENTER or doctor/physician if you feel unwell. Specific treatment: None known
If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention.
Take off contaminated clothing and wash before reuse.
Use dry chemical, water fog, CO₂, foam or sand/earth for extinction.

STORAGE Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool. Store locked up.

DISPOSAL Dispose of contents/container in accordance with local/regional/national/international regulation for hazardous wastes.

RV107x Rust Inhibitor

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 3 COMPOSITION/INFORMATION ON INGREDIENTS

CHEMICAL NAME	CAS #	%
HYDROTREATED LIGHT DISTILLATE (PETROLEUM)	64742-47-8	40-60
CARBON BLACK, AMORPHOUSE	1333-86-4	0.1-0.3

Note: Specific chemical identities and/or exact percentages have been withheld as a trade secret.

SECTION 4 FIRST AID MEASURES

INHALATION	If symptoms are experienced remove source of contamination or move victim to fresh air and obtain medical advice.
EYES	Flush eyes with plenty of water for at least 20 minutes retracting eyelids often. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Get immediate medical attention.
SKIN CONTACT	Wash with soap and water. Get medical attention if irritation develops or persists.
INGESTION	Do not induce vomiting and seek medical attention immediately. Provide medical care provider with this SDS. If vomiting occurs, lean victim forward to reduce risk of aspiration into lungs.
NOTE TO DOCTOR	Treat symptomatically.

SECTION 5 FIREFIGHTING MEASURES

EXTINGUISHING MEDIA	Use alcohol resistant foam, carbon dioxide, dry chemical, or water spray when fighting fires. Water or foam may cause frothing if liquid is burning but it still may be a useful extinguishing agent if carefully applied to the fire. Do not direct a water stream directly into the hot burning liquid.
FIRE AND/OR EXPLOSION HAZARDS	Vapors may be ignited by sparks, flames or other sources of ignition if material is above the flash point giving rise to a fire (Class B). Vapors are heavier than air and may travel to a source of ignition and flash back. Empty containers that retain product residue (liquid, solid/sludge, or vapor) can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose container to heat, flame, sparks, static electricity, or other sources of ignition. Any of these actions can potentially cause an explosion that may lead to injury or death.
FIRE FIGHTING METHODS AND PROTECTION	Do not enter fire area without proper protection including self-contained breathing apparatus and full protective equipment. Fight fire from a safe distance and a protected location due to the potential of hazardous vapors and decomposition products. Use appropriate methods for the surrounding fire.
HAZARDOUS COMBUSTION PRODUCTS	Oxides of carbon, Formaldehyde, Hydrocarbons, Calcium oxides, Sulfur oxides

SECTION 6 ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES	No health effects expected from the clean-up of this material, if contact can be avoided. Follow personal protective equipment recommendations found in Section VIII of this SDS
METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING UP	Absorb or cover with dry earth, sand or other non-combustible material and transfer to appropriate waste containers. Use clean, non-sparking tools to collect absorbed material. Collect and discard in accordance with local, state and national regulations.

SECTION 7 HANDLING AND STORAGE

PRECAUTIONS FOR SAFE HANDLING	Mildly irritating material. Avoid unnecessary exposure. As with all chemicals, good industrial hygiene practices should be followed when handling this material. Wash thoroughly after handling. Do not get in eyes, on skin and clothing. Ground and bond containers when transferring material. "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous.
CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES	Store in a cool dry place. Isolate from incompatible materials. Keep container closed when not in use. Keep away from heat, sparks, and flame.
INCOMPATIBLE MATERIALS	Strong oxidizing agents

RV107x Rust Inhibitor

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

CONTROL PARAMETERS

CHEMICAL NAME	ACGIH TLV	ACGIH STEL	OSHA PEL
HYDROTREATED LIGHT DISTILLATE (PETROLEUM)	212 ppm (8 hrs)		

US. OSHA TABLE Z-1 LIMITS FOR AIR CONTAMINATION (29 CFR 1910.1000)

COMPONENTS	TYPE	VALUE
Carbon Black, amorphous (CAS 1333-86-4)	PEL	3.5 mg.m3

US ACGIH THRESHOLD LIMIT VALUE

COMPONENTS	TYPE	VALUE
Carbon Black, amorphous (CAS 1333-86-4)	TWA	3 mg.m3

US NIOSH: POCKET GUIDE TO CHEMICAL HAZARDS

COMPONENTS	TYPE	VALUE
Carbon Black, amorphous (CAS 1333-86-4)	TWA	0.1 mg.m3

ENGINEERING MEASURES Local exhaust ventilation or other engineering controls are normally required when handling or using this product to avoid overexposure. Engineering controls must be designed to meet the OSHA chemical specific standard in 29 CFR 1910. Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits

RESPIRATORY PROTECTION Proper ventilation (at a minimum) will be required when handling this product. Use respirators (NIOSH approved) only if ventilation cannot be used to eliminate symptoms or reduce the exposure to below acceptable levels. Follow a respiratory protection program that meets 29 CFR 1910.134 and ANSI Z88.2 requirements whenever work place conditions warrant the use of a respirator.

EYE PROTECTION Wear chemically resistant safety glasses with side shields when handling this product. Do not wear contact lenses.

SKIN PROTECTION Not normally considered a skin hazard. Where use of product can result in skin contact, practice good personal hygiene and wear a barrier cream and/or impervious surgical style gloves. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work.

GLOVES Chemically resistant gloves

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES (TYPICAL, NOT SPECIFICATION)

PHYSICAL STATE	Viscous Liquid
COLOR	Black/Tan
ODOR	Slight Kerosene like
ODOR THRESHOLD	No data available
PH	No data available
MELTING POINT, °C	No data available
BOILING POINT, °C	No data available
FLASH POINT	>= 100 °F(38 °C)
EVAPORATION RATE	No data available
FLAMMABILITY (SOLID, GAS)	No data available
LOWER FLAMMABLE/EXPLOSIVE LIMIT, % IN AIR	No data available
UPPER FLAMMABLE/EXPLOSIVE LIMIT, % IN AIR	No data available
VAPOR PRESSURE	> 2 mmHg
VAPOR DENSITY	>1 (Air=1)
SPECIFIC GRAVITY @ 25°C	0.86
SOLUBILITY IN WATER	Negligible; 0-1%
OCTANOL/WATER PARTITION	No data available

RV107x Rust Inhibitor

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

COEFFICIENT

AUTOIGNITION TEMPERATURE	No data available
DECOMPOSITION TEMPERATURE	No data available
VISCOSITY	1800 cP
VOLATILES, % BY WEIGHT	52
VOC, LB/GAL	4.1
VOC, GRAMS/LITER	490

SECTION 10 STABILITY AND REACTIVITY

CHEMICAL STABILITY	Stable under normal conditions. Hazardous polymerization will not occur.
POSSIBILITY OF HAZARDOUS REACTIONS	Under normal conditions of storage and use, hazardous reactions will not occur.
CONDITIONS TO AVOID	Contamination. Elevated temperatures.
INCOMPATIBLE MATERIALS	Strong oxidizing agents
HAZARDOUS DECOMPOSITION PRODUCTS	Decomposition and hazardous decomposition products are unlikely.

SECTION 11 TOXICOLOGICAL INFORMATION

CARBON BLACK (1333-86-4)

IARC GROUP	2B - Possibly carcinogenic to humans
-------------------	--------------------------------------

LIKELY ROUTES OF ENTRY	Inhalation, Skin contact, Eye contact
TARGET ORGANS POTENTIALLY AFFECTED BY EXPOSURE	Central Nervous System
CHEMICAL INTERACTIONS THAT CHANGE TOXICITY	No chemical interaction known to affect toxicity.
MEDICAL CONDITIONS AGGRAVATED	Skin contact may aggravate existing skin disease, Respiratory disease including asthma and bronchitis
IMMEDIATE (ACUTE) HEALTH EFFECTS BY ROUTE OF EXPOSURE	
INHALATION IRRITATION	Can cause moderate respiratory irritation, dizziness, weakness, fatigue, nausea and headache. Other possible symptoms include; wheezing and coughing due to pulmonary edema (fluid build-up in lungs).
SKIN CONTACT	Can cause minor skin irritation, defatting, and dermatitis.
EYE CONTACT	Can cause moderate irritation, tearing and reddening, but not likely to permanently injure eye tissue.
INGESTION IRRITATION	Irritating to mouth, throat, and stomach. Can cause abdominal discomfort, nausea, vomiting and diarrhea. Aspiration of material into the lungs can cause chemical pneumonitis which can be fatal.
INGESTION TOXICITY	Harmful if swallowed.
LONG-TERM (CHRONIC) HEALTH EFFECTS	
CARCINOGENICITY	Possibly carcinogenic to humans
REPRODUCTIVE AND DEVELOPMENTAL TOXICITY	No data available to indicate product or any components present at greater than 0.1% may cause birth defects.
INHALATION	Upon prolonged and/or repeated exposure, can cause severe respiratory irritation, dizziness, weakness, fatigue, nausea, headache and possible unconsciousness.
SKIN CONTACT	Upon prolonged or repeated contact, can cause minor skin irritation, defatting, and dermatitis.

RV107x Rust Inhibitor

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

COMPONENT TOXICOLOGY DATA

CHEMICAL NAME

Hydrotreated light distillate (Petroleum)

CAS NUMBER

64742-47-8

LD50/LC50

Dermal LD50 Rabbit > 5000 mg/kg Oral LD50 Rat > 5000 mg/kg Inhalation LC50 (4h) Rat > 20 mg/L

SECTION 12 ECOLOGICAL INFORMATION

OVERVIEW No ecological information available

MOBILITY No data

PERSISTENCE No data

BIOACCUMULATION No data

DEGRADABILITY No data

ECOTOXICITY DATA

CHEMICAL NAME

CAS NUMBER

AQUATIC EC50 CRUSTACEA

AQUATIC ERC50 ALGAE

AQUATIC LC50 FISH

No data available

SECTION 13 DISPOSAL CONSIDERATIONS

WASTE DESCRIPTION FOR SPENT PRODUCT Spent or discarded material may be a hazardous waste.

DISPOSAL METHODS Dispose of by incineration following Federal, State, Local, or Provincial regulations.

WASTE DISPOSAL CODE(S) D001

SECTION 14 TRANSPORT INFORMATION

FULL SHIPPING NAME FOR EXPORT, AIR, SEA (ANY QUANTITY UNLESS FLASH PT. >150°F) OR VESSELS OF 119 GL OR MORE UN1263 Paint (including paint, lacquer, enamel, stain, shellac solutions, varnish, polish, liquid filler, and liquid lacquer base), 3, III

DOMESTIC GROUND IN VESSELS < 119 GAL. Not Regulated

SECTION 15 REGULATORY INFORMATION

TSCA STATUS All components in this product are on the TSCA Inventory or exempt.

CANADIAN DSL STATUS: All chemical substances in this material are included on or exempted from listing on the Canadian DSL.

CHEMICAL NAME

CAS

REGULATION

PERCENT

No 313-listed chemicals in this product

SARA 313

Carbon black (1333-86-4)

U.S. - California -
Proposition 65 -
Carcinogens List

U.S. - California -
Proposition 65 -
Developmental Toxicity

U.S. - California -
Proposition 65 -
Reproductive Toxicity -
Female

U.S. - California -
Proposition 65 -
Reproductive Toxicity -
Male

No significance risk level
(NSRL)

Yes

No

No

No

SECTION 16 OTHER INFORMATION

REVISION DATE 05/30/2018

DISCLAIMER Although the information contained herein is believed to be reliable, it is furnished without warranty of any kind. This information is not intended to be all-inclusive as to the manner and conditions of use, handling, and storage.

VERSION COMMENTS Revised
Approved: DW