

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name : 2000 Ultra Premium Coating

Product form : Mixture

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### 1.3. Details of the supplier of the safety data sheet

Inland Coatings Holdings, LLC  
26259 US-6  
Adel, Iowa 50003  
800-456-8467

#### 1.4. Emergency telephone number

CHEMTREC : 800-424-9300

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### GHS-US classification

Flam. Liq. 2	H225
Acute Tox. 4 (Inhalation)	H332
Skin Irrit. 2	H315
Eye Irrit. 2A	H319
Skin Sens. 1	H317
Muta. 1B	H340
Carc. 1A	H350
STOT SE 3	H336
STOT RE 1	H372
Asp. Tox. 1	H304

#### 2.2. Label elements

##### GHS-US labelling

Hazard pictograms (GHS-US) :



GHS02



GHS07



GHS08

Signal word (GHS-US) : **Danger**

Hazard statements (GHS-US) :

- H225 - Highly flammable liquid and vapour
- H304 - May be fatal if swallowed and enters airways
- H315 - Causes skin irritation
- H317 - May cause an allergic skin reaction
- H319 - Causes serious eye irritation
- H332 - Harmful if inhaled
- H336 - May cause drowsiness or dizziness
- H340 - May cause genetic defects
- H350 - May cause cancer
- H372 - Causes damage to organs through prolonged or repeated exposure

Precautionary statements (GHS-US) :

- P201 - Obtain special instructions before use
- P202 - Do not handle until all safety precautions have been read and understood
- P210 - Keep away from heat, hot surfaces, open flames, sparks. - No smoking
- P240 - Ground/bond container and receiving equipment
- P241 - Use explosion-proof electrical, lighting, ventilating equipment
- P242 - Use only non-sparking tools
- P243 - Take precautionary measures against static discharge
- P260 - Do not breathe mist, spray, vapours
- P264 - Wash hands, forearms and face thoroughly after handling
- P270 - Do not eat, drink or smoke when using this product
- P271 - Use only outdoors or in a well-ventilated area
- P280 - Wear eye protection, protective clothing, protective gloves
- P301+P310 - IF SWALLOWED: Immediately call a doctor, a poison center
- P302+P352 - If on skin: Wash with plenty of soap and water
- P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower
- P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing

# 2000 Ultra Premium Coating

## Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P308+P313 - If exposed or concerned: Get medical advice/attention

P314 - Get medical advice/attention if you feel unwell

P321 - Specific treatment (see first aid instructions on this label)

P331 - Do NOT induce vomiting

P333+P313 - If skin irritation or rash occurs: Get medical advice/attention

P337+P313 - If eye irritation persists: Get medical advice/attention

P362+P364 - Take off contaminated clothing and wash it before reuse

P370+P378 - In case of fire: Use carbon dioxide (CO<sub>2</sub>), dry extinguishing powder, foam to extinguish

P403+P233+235 - Store in a well-ventilated place. Keep container tightly closed. Keep cool.

P405 - Store locked up

P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

### 2.3. Other hazards

No additional information available

### 2.4. Unknown acute toxicity (GHS-US)

16.6% of the mixture is of unknown acute toxicity

## SECTION 3: Composition/information on ingredients

### 3.1. Substance

Not applicable

### 3.2. Mixture

Name	Product identifier	%
Naphtha, petroleum, hydrotreated light	(CAS No) 64742-49-0	25 - 50
Xylenes (o-, m-, p- isomers)	(CAS No) 1330-20-7	3- 7
Solvent naphtha, petroleum, light aromatic	(CAS No) 64742-95-6	5 - 15
Ethylbenzene	(CAS No) 100-41-4	1 - 5
Benzene, 1,2,4-trimethyl-	(CAS No) 95-63-6	2 - 6
Cumene	(CAS No) 98-82-8	0.1 - .5
Titanium dioxide	(CAS No) 13463-67-7	8 - 15
Silica: Crystalline, quartz	(CAS No) 14808-60-7	0.1 - 1
Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	(CAS No) 41556-26-7	0.1 - 1

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

**First-aid measures general** : If exposed or concerned, get medical attention/advice. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before re-use. Never give anything to an unconscious person.

**First-aid measures after inhalation** : IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if breathing is affected. If breathing is difficult, supply oxygen.

**First-aid measures after skin contact** : IF ON SKIN (or clothing): Remove affected clothing and wash all exposed skin with water for at least 15 minutes. If irritation develops or persists, get medical attention.

**First-aid measures after eye contact** : IF IN EYES: Immediately flush with plenty of water for at least 15 minutes. Remove contact lenses if present and easy to do so. If pain, blinking, or irritation develops or persists, get medical attention. Continue rinsing.

**First-aid measures after ingestion** : IF SWALLOWED: rinse mouth thoroughly. Do not induce vomiting without advice from poison control center or medical professional. Get medical attention immediately.

### 4.2. Most important symptoms and effects, both acute and delayed

**Symptoms/injuries after inhalation** : May be fatal if swallowed and enters airways. Harmful if inhaled. May cause drowsiness or dizziness.

**Symptoms/injuries after skin contact** : May cause an allergic skin reaction. Causes skin irritation.

**Symptoms/injuries after eye contact** : Causes serious eye irritation.

**Symptoms/injuries after ingestion** : May be fatal if swallowed and enters airways.

**Chronic symptoms** : May cause cancer (Inhalation). Causes damage to organs through prolonged or repeated exposure.

### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

# 2000 Ultra Premium Coating

## Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

**Suitable extinguishing media** : Foam. Dry powder. Carbon dioxide.

**Unsuitable extinguishing media** : Water.

#### 5.2. Special hazards arising from the substance or mixture

**Fire hazard** : Flammable liquid and vapour.

**Reactivity** : Closed container may forcibly rupture under extreme heat or when contents are contaminated with water.

#### 5.3. Advice for firefighters

**Firefighting instructions** : Exercise caution when fighting any chemical fire. Do not dispose of fire-fighting water in the environment. Prevent human exposure to fire, fumes, smoke and products of combustion.

**Protection during firefighting** : Do not enter fire area without proper protective equipment, including respiratory protection.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

**General measures** : Evacuate area. Keep upwind. Ventilate area. Spill should be handled by trained clean-up crews properly equipped with respiratory equipment and full chemical protective gear (see Section 8). Avoid vapor formation.

##### 6.1.1. For non-emergency personnel

**Protective equipment** : Wear Protective equipment as described in Section 8.

**Emergency procedures** : Evacuate unnecessary personnel.

##### 6.1.2. For emergency responders

**Protective equipment** : Wear suitable protective clothing, gloves and eye or face protection. Approved supplied-air respirator, in case of emergency.

#### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Avoid release to the environment.

#### 6.3. Methods and material for containment and cleaning up

**For containment** : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

**Methods for cleaning up** : Remove all sources of ignition. Avoid breathing of vapors. Wear appropriate respirator and other protective clothing. Ventilate. Shut off source of leak only if safe to do so. Soak up with absorbent material, and place in non-leaking containers for proper disposal.

#### 6.4. Reference to other sections

No additional information available

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

**Precautions for safe handling** : Keep away from heat, sparks and open flames. Use adequate ventilation and avoid repeated or prolonged skin contact. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour.

#### 7.2. Conditions for safe storage, including any incompatibilities

**Storage conditions** : Store in a well-ventilated place. Keep container tightly closed. Isolate from oxidizers, heat, sparks, electrical equipment and open flame. Closed containers may explode if exposed to extreme heat.

# 2000 Ultra Premium Coating

## Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

<b>Naphtha, petroleum, hydrotreated light (64742-49-0)</b>	
Remark (ACGIH)	OELs not established
Remark (OSHA)	OELs not established
<b>Xylenes (o-, m-, p- isomers) (1330-20-7)</b>	
ACGIH TWA (ppm)	100 ppm
ACGIH STEL (ppm)	150 ppm
OSHA PEL (TWA) (mg/m <sup>3</sup> )	435 mg/m <sup>3</sup>
OSHA PEL (TWA) (ppm)	100 ppm
OSHA PEL (STEL) (mg/m <sup>3</sup> )	655 mg/m <sup>3</sup>
OSHA PEL (STEL) (ppm)	150 ppm
<b>Ethylbenzene (100-41-4)</b>	
ACGIH TWA (ppm)	20 ppm
Remark (ACGIH)	upper respiratory tract irritation; kidney damage (nephropathy); cochlear impairment
OSHA PEL (TWA) (mg/m <sup>3</sup> )	435 mg/m <sup>3</sup>
OSHA PEL (TWA) (ppm)	100 ppm
OSHA PEL (STEL) (mg/m <sup>3</sup> )	545 mg/m <sup>3</sup>
OSHA PEL (STEL) (ppm)	125 ppm
<b>Cumene (98-82-8)</b>	
ACGIH TWA (ppm)	50 ppm
OSHA PEL (TWA) (mg/m <sup>3</sup> )	245 mg/m <sup>3</sup>
OSHA PEL (TWA) (ppm)	50 ppm
<b>Solvent naphtha, petroleum, light aromatic (64742-95-6)</b>	
Remark (ACGIH)	OELs not established
Remark (OSHA)	OELs not established
<b>Benzene, 1,2,4-trimethyl- (95-63-6)</b>	
Remark (ACGIH)	OELs not established
Remark (OSHA)	OELs not established
<b>Silica: Crystalline, quartz (14808-60-7)</b>	
ACGIH TWA (mg/m <sup>3</sup> )	0.025 mg/m <sup>3</sup> (respirable fraction)
OSHA PEL (TWA) (mg/m <sup>3</sup> )	(30)/(%SiO <sub>2</sub> + 2) total dust; (10)/(%SiO <sub>2</sub> + 2) respirable fraction
OSHA PEL (TWA) (ppm)	(250)/(%SiO <sub>2</sub> + 5) respirable fraction
<b>Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate (41556-26-7)</b>	
Remark (ACGIH)	OELs not established
Remark (OSHA)	OELs not established
<b>Titanium dioxide (13463-67-7)</b>	
ACGIH TWA (mg/m <sup>3</sup> )	10
OSHA PEL (TWA) (mg/m <sup>3</sup> )	15 total dust

#### 8.2. Exposure controls

**Appropriate engineering controls** : Provide adequate general and local exhaust ventilation. Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Use explosion-proof equipment with flammable materials. Ensure adequate ventilation, especially in confined areas.

**Personal protective equipment** : Safety glasses. Gloves. Protective clothing. Insufficient ventilation: wear respiratory protection.



# 2000 Ultra Premium Coating

## Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

- Hand protection** : Use gloves chemically resistant to this material when prolonged or repeated contact could occur. Gloves should be classified under Standard EN 374 or ASTM F1296. Suggested glove materials are: Neoprene, Nitrile/butadiene rubber, Polyethylene, Ethyl vinyl alcohol laminate, PVC or vinyl.
- Eye protection** : Wear eye protection, including chemical splash goggles and a face shield when possibility exists for eye contact due to spraying liquid or airborne particles.
- Skin and body protection** : Wear long sleeves, and chemically impervious PPE/coveralls to minimize bodily exposure.
- Respiratory protection** : Wear a NIOSH-approved (or equivalent) full-facepiece airline respirator in the positive pressure mode with emergency escape provisions. In case of inadequate ventilation or risk of inhalation of vapors, use suitable respiratory equipment with gas filter (type A2). Use a positive-pressure air-supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air-purifying respirators may not provide adequate protection.

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

- Physical state** : Liquid
- Color** : White/Gray
- Odor** : aromatic.
- Odor Threshold** : No data available
- pH** : No data available
- Relative evaporation rate (butylacetate=1)** : No data available
- Relative evaporation rate (ether=1)** : Slower than ether
- Melting point** : No data available
- Freezing point** : No data available
- Boiling point** : 118.3 - 172.2 °C (245-342 °F)
- Flash point** : 12.22 °C TCC (54 °F)
- Auto-ignition temperature** : No data available
- Decomposition temperature** : No data available
- Flammability (solid, gas)** : No data available
- Vapour pressure** : 5.2 mm Hg At 20 °C
- Relative vapour density at 20 °C** : No data available
- Relative density** : 1.007
- Density** : 8.4 pounds/gallon
- Relative gas density** : Heavier than air
- Solubility** : Water: Slight
- Log Pow** : No data available
- Log Kow** : No data available
- Viscosity, kinematic** : No data available
- Viscosity, dynamic** : No data available
- Explosive properties** : No data available
- Oxidising properties** : No data available
- Explosive limits** : 0.9 - 6 vol %

#### 9.2. Other information

- VOC content** : 550 g/l maximum

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

Closed container may forcibly rupture under extreme heat or when contents are contaminated with water.

#### 10.2. Chemical stability

Stable under recommended handling and storage conditions (see section 7).

#### 10.3. Possibility of hazardous reactions

None known.

#### 10.4. Conditions to avoid

Heat, flame.

# 2000 Ultra Premium Coating

## Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 10.5. Incompatible materials

Strong oxidizers, strong acids and some amines.

### 10.6. Hazardous decomposition products

Carbon oxides (CO, CO<sub>2</sub>).

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

**Acute toxicity** : Inhalation: Harmful if inhaled.

Naphtha, petroleum, hydrotreated light (64742-49-0)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 3160 mg/kg
LC50 inhalation rat (ppm)	73680 ppm/4h
Xylenes (o-, m-, p- isomers) (1330-20-7)	
LD50 oral rat	3500 mg/kg
ATE CLP (dermal)	1100.000 mg/kg bodyweight
ATE CLP (gases)	4500.000 ppmv/4h
ATE CLP (vapours)	11.000 mg/l/4h
ATE CLP (dust,mist)	1.500 mg/l/4h
Ethylbenzene (100-41-4)	
LD50 oral rat	3500 mg/kg
LD50 dermal rabbit	15400 mg/kg
LC50 inhalation rat (mg/l)	17.2 mg/l/4h
ATE CLP (gases)	4500.000 ppmv/4h
ATE CLP (vapours)	11.000 mg/l/4h
ATE CLP (dust,mist)	1.500 mg/l/4h
Cumene (98-82-8)	
LD50 dermal rabbit	12300 µl/kg
LC50 inhalation rat (ppm)	> 3577 ppm 6 h
Solvent naphtha, petroleum, light aromatic (64742-95-6)	
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat (ppm)	3400 ppm/4h
Benzene, 1,2,4-trimethyl- (95-63-6)	
LD50 oral rat	3280 mg/kg
LD50 dermal rabbit	> 3160 mg/kg
ATE CLP (gases)	4500.000 ppmv/4h
ATE CLP (vapours)	11.000 mg/l/4h
ATE CLP (dust,mist)	1.500 mg/l/4h
Silica: Crystalline, quartz (14808-60-7)	
LD50 oral rat	500 mg/kg
ATE CLP (oral)	500.000 mg/kg bodyweight
Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate (41556-26-7)	
LD50 oral rat	2615 mg/kg
Titanium dioxide (13463-67-7)	
LD50 oral rat	> 10000 mg/kg

**Skin corrosion/irritation** : Causes skin irritation.

**Serious eye damage/irritation** : Causes serious eye irritation.

**Respiratory or skin sensitisation** : May cause an allergic skin reaction.

**Germ cell mutagenicity** : May cause genetic defects.

**Carcinogenicity** : May cause cancer.

Ethylbenzene (100-41-4)	
IARC group	2B - Possibly carcinogenic to humans

# 2000 Ultra Premium Coating

## Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>Cumene (98-82-8)</b>	
IARC group	2B - Possibly carcinogenic to humans
<b>Silica: Crystalline, quartz (14808-60-7)</b>	
IARC group	1 - Carcinogenic to humans
<b>Carbon black (1333-86-4)</b>	
IARC group	2B - Possibly carcinogenic to humans
<b>Titanium dioxide (13463-67-7)</b>	
IARC group	2B - Possibly carcinogenic to humans

**Reproductive toxicity** : Not classified

**Specific target organ toxicity (single exposure)** : May cause drowsiness or dizziness.

**Specific target organ toxicity (repeated exposure)** : Causes damage to organs through prolonged or repeated exposure.

**Aspiration hazard** : May be fatal if swallowed and enters airways.

**Symptoms/injuries after inhalation** : May be fatal if swallowed and enters airways. Harmful if inhaled. May cause drowsiness or dizziness.

**Symptoms/injuries after skin contact** : May cause an allergic skin reaction. Causes skin irritation.

**Symptoms/injuries after eye contact** : Causes serious eye irritation.

**Symptoms/injuries after ingestion** : May be fatal if swallowed and enters airways.

**Chronic symptoms** : May cause cancer (Inhalation). Causes damage to organs (respiratory system) through prolonged or repeated exposure.

### SECTION 12: Ecological information

#### 12.1. Toxicity

**Ecology - general** : No data available.

#### 12.2. Persistence and degradability

##### 2000 Ultra Premium Coating

Persistence and degradability	The product is not biodegradable.
-------------------------------	-----------------------------------

#### 12.3. Bioaccumulative potential

No additional information available

#### 12.4. Mobility in soil

No additional information available

#### 12.5. Other adverse effects

No additional information available

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

**Waste treatment methods** : Do not discharge to public wastewater systems without permit of pollution control authorities. No discharge to surface waters is allowed without an NPDES permit.

**Waste disposal recommendations** : Dispose in a safe manner in accordance with local/national regulations. Do not allow the product to be released into the environment.

### SECTION 14: Transport information

#### In accordance with DOT

**Transport document description** : UN1263 Paint (including paint, lacquer, enamel, stain, shellac solutions, varnish, polish, liquid filler, and liquid lacquer base), 3, II

**UN-No.(DOT)** : 1263

**DOT NA no.** :

**UN1263**

**Proper Shipping Name (DOT)** : Paint

including paint, lacquer, enamel, stain, shellac solutions, varnish, polish, liquid filler, and liquid lacquer base.

**Department of Transportation (DOT) Hazard Classes** : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

# 2000 Ultra Premium Coating

## Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

**Hazard labels (DOT) :** 3 - Flammable liquid



**Packing group (DOT) :** II - Medium Danger

**DOT Quantity Limitations Passenger :** 5 L  
aircraft/rail (49 CFR 173.27)

**DOT Quantity Limitations Cargo aircraft only :** 60 L  
(49 CFR 175.75)

**DOT Vessel Stowage Location :** B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.

### Additional information

**Other information :** No supplementary information available.

### Transport by sea

No additional information available

### Air transport

No additional information available

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

#### 2000 Ultra Premium Coating

All components of this product are listed on the TSCA Inventory or are exempt

SARA Section 311/312 Hazard Classes

Delayed (chronic) health hazard  
Immediate (acute) health hazard  
Fire hazard

	<b>CAS #:</b> 1330-20-7 (Xylenes)
Section 302 (EHS) TPQ	lb
Section 304 EHS RQ	lb
CERCLA RQ	100 lb
Section 313	Listed on US SARA Section 13

	<b>CAS #:</b> 100-41-4 (Ethylbenzene)
Section 302 (EHS) TPQ	lb
Section 304 EHS RQ	lb
CERCLA RQ	1000 lb
Section 313	Listed on US SARA Section 13

	<b>CAS #:</b> 98-82-8 (Cumene)
Section 302 (EHS) TPQ	lb
Section 304 EHS RQ	lb
CERCLA RQ	5000 lb
Section 313	Listed on US SARA Section 13

	<b>CAS #:</b> 95-63-6 (Benzene, 1,2,4—trimethyl-)
Section 302 (EHS) TPQ	lb
Section 304 EHS RQ	lb
CERCLA RQ	lb
Section 313	Listed on US SARA Section 13

# 2000 Ultra Premium Coating

## Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 2000 Ultra Premium Coating

	<b>CAS #:</b> 108-88-3 (Toluene)
Section 302 (EHS) TPQ	lb
Section 304 EHS RQ	lb
CERCLA RQ	1000 lb
Section 313	Listed on US SARA Section 13

	<b>CAS #:</b> 50-00-0 (Formaldehyde)
Section 302 (EHS) TPQ	500 lb
Section 304 EHS RQ	100 lb
CERCLA RQ	100 lb
Section 313	Listed on US SARA Section 13

	<b>CAS #:</b> 78-83-1 (Isobutyl alcohol)
Section 302 (EHS) TPQ	lb
Section 304 EHS RQ	lb
CERCLA RQ	5000 lb
Section 313	Not Listed

	<b>CAS #:</b> 123-86-4 (n-Butyl acetate)
Section 302 (EHS) TPQ	lb
Section 304 EHS RQ	lb
CERCLA RQ	5000 lb
Section 313	Not Listed

### 15.2. International regulations

No additional information available.

### 15.3. US State regulations

#### California Proposition 65

WARNING! This product contains chemicals known to the state of California to cause cancer, birth defects, or other reproductive harm.

#### Ethylbenzene (100-41-4)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes	No	No	No	

#### Cumene (98-82-8)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes	No	No	No	

#### Silica: Crystalline, quartz (14808-60-7)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes	No	No	No	

#### Carbon black (1333-86-4)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes	No	No	No	

# 2000 Ultra Premium Coating

## Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>Titanium dioxide (13463-67-7)</b>				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes	No	No	No	NA
<b>Toluene (108-88-3)</b>				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
No	Yes	No	No	
<b>Formaldehyde (50-00-0)</b>				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes	No	No	No	
<b>Benzene</b>				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes	Yes	No	Yes	
<b>Napthalene</b>				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes	No	No	No	
<b>Xylenes (o-, m-, p- isomers) (1330-20-7)</b>				
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List				
<b>Ethylbenzene (100-41-4)</b>				
U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Massachusetts - Right To Know List U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List				
<b>Benzene, 1,2,4-trimethyl- (95-63-6)</b>				
U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Massachusetts - Right To Know List U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List				
<b>Talc (14807-96-6)</b>				
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List				
<b>Titanium dioxide (13463-67-7)</b>				
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List				
<b>Carbon black (1333-86-4)</b>				
U.S. - New Jersey - Right to Know Hazardous Substance List				

# 2000 Ultra Premium Coating

## Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 16: Other information

**Indication of changes** : Version: 1.0


**Revision date** : 05/30/2018

**Other information** : Author: DW

**NFPA health hazard** : 3 - Short exposure could cause serious temporary or residual injury even though prompt medical attention was given.

**NFPA fire hazard** : 3 - Liquids and solids that can be ignited under almost all ambient conditions.

**NFPA reactivity** : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



### HMIS III Rating

**Health** : 3\*

**Flammability** : 3

**Physical** : 0

**Personal Protection** :

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product