



AS364

Fire Sounder, Multi Tone, Deep Base

General

The AS364 is a general purpose electronic sounder for fire alarm applications. Which features a special base containing all wiring connections and allow for easy removal/placement of the sounder.

Easy and Fast Installation

The AS364 alarm sounder allows faster installation and maintenance thanks to an innovative mounting base. Dispensing with the need for locking screws, these sounders use a deep base version of the TimeSaver™ base from the 630 series detectors. Heads are simply locked onto the base with a “twist and click” action, allowing fitting or removal at any time because the base is the only component that needs to be wired. As the cabling requirement is reduced, commissioning time and costs are naturally reduced as well.

Efficient and versatile

The AS364 provide high sound output at a low current, thus reducing power requirements and system cost. The AS364 sounder is supplied with a volume control as standard, allowing final audio adjustments to be made during installation.

With a choice of 32 different tones (see tones table in manual), which are switch selectable, the required tone can be selected during installation. A second tone, is available if extra wires are installed in the sounder circuit.

The mechanism for locking the sounder to the base, can be activated if required. Once activated, a special tool is required to remove the sounder from the base.



Details

- High sound output
- Low current consumption
- 32 Tones user selectable
- Automatic synchronisation
- Volume control
- Anti-Tamper locking mechanism
- Deep mouting base
- Wiring directly to base
- Two stage alarm
- VdS Approved

AS364

Fire Sounder, Multi Tone, Deep Base

Technical specifications

Electrical

Current consumption 4 - 41mA @ 24 VDC

Sounder

Selectable tones 32

General

Line monitoring polarised input

Physical

Physical dimensions 100 x 104 mm (Ø x D)

Net weight 250 g

Colour Red

Material High impact polycarbonate

Environmental

Operating temperature -25 to +70°C

Environment Indoor, Outdoor

IP rating IP65

Standards & regulation

Certification EN54-3

Operation

Continuous

Supply voltage

EN54-3 / fire applications 17 - 60 VDC

non-fire applications 9 - 60 VDC

Sound output @ 1 metre

(see tone table in manual) 94 to 106dB(A)

Automatic synchronisation

Phased start

