

	<p>Chamfers the outside diameters of bars and tubes Range 8-28mm</p>
---	--

Packed Weight and Dimensions

Code	Description	Weight g	W mm	H mm	L mm
NG 3500	Heavy Duty External Rotodrive	117	52	73	198

	<p><b>Instructions</b></p> <p>Do not use heavy pressure when deburring as this will cause the blade to dig into the material and give an uneven finish Use light and even pressure which will allow the blade and handle to work together to remove the burr and leave a smooth finish on the component</p> <p>Blades should be handled carefully as they are sharp and can cut Blades can break causing flying objects Sharp edges and flying objects can cause injury Users and bystanders should wear protective safety glasses Do not pry or bend blades Keep blades and sharp tools away from children Do not regrind blades as this will weaken the blade and cause breakage and possible injury</p> <p>All Noga products meet the strict requirements of ISO 9001 and ISO 14001</p>
---	--

NG-3 Handle


	<p>NG-3 Handle accepts all Blade Holders Ergonomic soft grip, acetyl and rubber construction Removable end cap for blade storage 125mm long x 28mm maximum diameter</p>
---	---

Packed Weight and Dimensions

Code	Description	Weight g	W mm	H mm	L mm
NG-3 Handle	NG3000	45	32	32	153

Heavy Duty External Rotodrive

HD External Rotodrive Holder

	<p>Holds EX 3001 External Chamfering Head Used in NG-3 Handle</p>
---	---

Packed Weight and Dimensions

Code	Description	Weight g	W mm	H mm	L mm
EL 00902	HD External Rotodrive Holder	40	65	35	95

EX 3001

		<p>90° External Rotodrive Chamfer Head Range: 8-28mm diameter Internal Thread M7 Blade material: HSS M2 Blade hardness: 62-64 HRC Used with HD Rotodrive Holder E0802 And NG-3 Handle</p>
---	--	---

Packed Weight and Dimensions

Code	Description	Weight g	W mm	H mm	L mm
EX 3001	External Chamfering Head 8-28mm	16	36	23	71