


Screw Plug Gauges UNC & UNF

	<p>Screw Plug Gauges:</p> <p>ISO Threads 6H Tolerance Red band on NO-GO end</p>
---	---

Screw Plug Gauges UNC

Code	Size	Go Pitch Diameter	No-Go Pitch Diameter	Class
53-810-000	4 – 40 UNC	0.0958"	0.0991"	2B
53-810-001	¼ - 20 UNC	0.2175"	0.2223"	2B
53-810-002	5/16 – 18 UNC	0.2764"	0.2817"	2B
53-810-003	3/8 – 16 UNC	0.3344"	0.3401"	2B
53-810-004	½ - 13 UNC	0.4500"	0.4565"	2B

Packed Weight and Dimensions

Code	Size	Weight g	W mm	H mm	L mm
53-810-000	4 – 40 UNC	9	11	11	94
53-810-001	¼ - 20 UNC	27	15	15	101
53-810-002	5/16 – 18 UNC	29	24	24	92
53-810-003	3/8 – 16 UNC	48	15	15	104
53-810-004	½ - 13 UNC	60	24	24	113

Screw Plug Gauges UNF

Code	Size	Go Pitch Diameter	No-Go Pitch Diameter	Class
53-820-001	¼ - 28 UNF	0.2268"	0.2311"	2B
53-820-002	5/16 – 24 UNF	0.2854"	0.2902"	2B
53-820-003	3/8 – 24 UNF	0.3479"	0.3528"	2B
53-820-005	7/16 – 20 UNF	0.4050"	0.4104"	2B
53-820-004	½ - 20 UNF	0.4675"	0.4731"	2B

Packed Weight and Dimensions

Code	Size	Weight g	W mm	H mm	L mm
53-820-001	¼ - 28 UNF	27	15	15	101
53-820-002	5/16 – 24 UNF	29	15	15	100
53-820-003	3/8 – 24 UNF	48	15	15	104
53-820-005	7/16 – 20 UNF	48	24	24	100
53-820-004	½ - 20 UNF	75	24	24	107