Product: Noga Leader: NG 3800 Page 1 of 2



Used to produce a 45° chamfer on straight or curved edges

Date: 26-03-2013

Includes: NG-3 Handle, LD Holder and L1 Blade

Packed Weight and Dimensions

Code	Description	Weight g	W mm	H mm	L mm
NG 3800	Leader	89	30	30	180



Instructions

Do not use heavy pressure when deburring as this will cause the blade to dig into the material and give an uneven finish

Use light and even pressure which will allow the blade and handle to work together to remove the burr and leave a smooth finish on the component

Blades should be handled carefully as they are sharp and can cut

Blades can break causing flying objects

Sharp edges and flying objects can cause injury

Users and bystanders should wear protective safety glasses

Do not pry or bend blades

Keep blades and sharp tools away from children

Do not regrind blades as this will weaken the blade and cause breakage and possible injury

All Noga products meet the strict requirements of ISO 9001 and ISO 14001

NG-3 Handle



NG-3 Handle accepts all Blade Holders Ergonomic soft grip, acetyl and rubber construction Removable end cap for blade storage 125mm long x 28mm maximum diameter

Packed Weight and Dimensions

Code	Description	Weight g	W mm	H mm	L mm
NG-3 Handle	NG3000	45	32	32	153

LD Holder



Holds L1 Blade Used in NG-3 Handle Telescopes from 30 to 115mm in Handle

Packed Weight and Dimensions

Code	Description	Weight g	W mm	H mm	L mm
EL 07505	LD Holder	50	23	23	153

Copyright: Linear Tools 2013

Data Sheet: LDS 1390

Product: Noga Leader: NG 3800 Page 2 of 2

L1 Blade





Replacement Blade for the Noga LEADER Tool (NG 3800)

Date: 26-03-2013

Works best on steel and aluminium

Material: HSS

Hardness: 62 - 64 HRC Included Angle: 45°

Fits to LD Holder (ELO7505)

Packed Weight and Dimensions

Code	Description	Pack	Weight g	W mm	H mm	L mm
		Quantity				
BL1001	Replacement Blade for Leader	10	16	62	10	130

Copyright: Linear Tools 2013