



DEEP ROOF LIGHTING INC.
P.O. BOX 520191, FLUSHING, NY 11352
Tel: 516-676-9100, 9101, 9103, 9105, 9106
Fax: 516-676-9109

Web Site: www.deeprooflighting.org www.deeprooflighting.com

Email: deeproof@aol.com deeproofgg@gmail.com

LED High Bay Platter - ETL DLC



Construction:


- 0.8mm steel housing
- 1.2mm aluminum heatsink
- Poly carbonate Lens
- Isolated LED driver
- Epistar 2835 LED chips
- Option: Wire Guard Acrylic Cover



Electrical control:

- Input voltage range: 100-277V AC
- Frequency: 50-60Hz
- Power factor: >0.95
- Harmonic Distortion: THD<13%
- Optional: Micro wave motion sensor
Emergency battery back up

CRI
>83



Wattage	Size	Dimensions(mm)	Voltage	Lumens
160W	4'	1220X285X100	100-277V	16000-18400lm
240W	4'	1220X410X100	100-277V	24000-27600lm
200W	5'	1520X285X100	100-277V	20000-23000lm
300W	5'	1520X410X100	100-277V	30000-34500lm

Option - Dimmable (0-10 VDC) --- ETL DLC

Option - Dimmable (0-10 VDC) and Occupation Sensor (OS) ---- ETL



Integrated LED array covered by frosted circular lenses.

Fixture surface protected fully with clear lenses facade



ITEM CODES

LHBP-G440-A(40/50/60)	4 feet, 160W, 4 X 40W, 100-277 VAC, 16000-18400 Lumen, (4000/5000/6000K)
LHBP-G640-A(40/50/60)	4 feet, 240W, 6 X 40W, 100-277 VAC, 24000-27600 Lumen, (4000/5000/6000K)
LHBP-G440-D(40/50/60)	160W, 4 X 40W, 16000-18400 Lumen, (4000/5000/6000K), Dimmable
LHBP-G640-D(40/50/60)	240W, 6 X 40W, 24000-27600 Lumen, (4000/5000/6000K), Dimmable
LHBP-G440-D(40/50/60)-OS	160W, 4 X 40W, 16000-18400 Lumen, (4000/5000/6000K), Dimmable, Ocp sensor
LHBP-G640-D(40/50/60)-OS	240W, 6 X 40W, 24000-27600 Lumen, (4000/5000/6000K), Dimmable, Ocp sensor
LHBP-G450-A(40/50/60)	5 feet, 200W, 4 X 50W, 100-277 VAC, 20000-23000 Lumen, (4000/5000/6000K)
LHBP-G650-A(40/50/60)	5 feet, 300W, 6 X 50W, 100-277 VAC, 30000-34500 Lumen, (4000/5000/6000K)



LHBP-CHAN By meter, Suspension Chain
2 per fixture



LHBP-BRKT Ceiling Bracket
2 per fixture



LHBP-POWR By Meter, Power cable



LHBP-WG44 Wire Guard for 4 feet 4 lines
LHBP-WG46 Wire Guard for 4 feet 6 lines
LHBP-WG54 Wire Guard for 5 feet 4 lines
LHBP-WG56 Wire Guard for 5 feet 6 lines



LHBP-PC44 Clear Plastic Cove for 4 feet 4 lines
LHBP-PC46 Clear Plastic Cove for 4 feet 6 lines
LHBP-PC54 Clear Plastic Cove for 5 feet 4 lines
LHBP-PC56 Clear Plastic Cove for 5 feet 6 lines