

Pillar Light ULTRA

PIL/U

DESCRIPTION

The Ultra Pillar Light illuminates both upwards and downwards, giving columns, gateway pillars and entrances a dramatic effect.

All Hunza products have an extra layer of powdercoat to ensure maximum corrosion protection.



PURE LED

LED Chip	Cree CXA Plug and Play, field replaceable PCB boards, 2x37Vf
Output	2x1400 lumens @ 700mA max
Lumens Per Watt	80 lm/W
Power Consumption	52 watts
Colour Temperature	2700K, 3000K and 4000K
CRI Warm White (3000K)	85+
Beam Angle	13, 22, 33, 51 Degrees


PHYSICAL PROPERTIES

Materials	Powdercoated Aluminium
Ingress Protection	IP66+
Impact Resistance	IK10
Standards	AS/NZS 61046, UL 1598, CSA C22.2 No. 250.0

POWER SUPPLY OPTIONS

NO DRIVER REQ FOR RETRO 'R' (INTEGRAL 230V IN) | DRIVER REQ FOR SERIES WIRED (CC FORMAT) **

** Contact sales office



CATEGORY
ARCHITECTURAL ULTRA RANGE

LUMINAIRE

PIL/U

POWER

- /L/S 700mA INPUT (CC) SERIES WIRED
- /L/R RETRO, 110/240V DRIVER

BEAM

COLOUR

- 22
- 33
- 51
- 13

ACCESSORIES

- 2 2700K
- 3 3000K
- 4 4000K
- 39 3000K, 90+ CRI
- HCL HEX CELL LOUVRE
- SNT SNOOT
- GG GLARE GUARD
- GS05 GLARE SHIELD
- FL FROSTED LENS
- CIK CABLE JOINT KIT

MATERIAL/ FINISH

- BK BLACK
- BZ BRONZE
- OGR OLIVE GREEN
- WH WHITE
- WB WHITE BIRCH
- DG DARK GREY
- STAR SILVER STAR
- CT CORTEN

/L/S PURELED SERIES WIRED

Constant current driver (included-700mA). Individual fixture require 74VDC @ 700mA maximum. 0-10 volt dimming.

/L/R PURELED 110/277VAC RETRO DRIVER

Constant current driver (included). Input: 240 VAC. Output: 60 watts total 74VDC @ 700mA 0-10 volt dimming.

Requires Lens
Ring extension

PRODUCT CONFIGURATION

5