

# Lawn Light Deck Mount

## DESCRIPTION

The Lawn Light Deck Mount version is designed to be mounted into timber decks. The luminaire can be walked upon without risk of damage. The lamp can be directed up to 20 degrees at a bush, tree, or the outside of a building etc. The flush fit lens stops water pooling and depositing dirt on the lens.

LLDMV

### PURE LED

LED Chip	Cree XHP-50-2 Plug and Play, field replaceable LED board, 6Vf
Output	600lumens @ 1050mA max
Lumens Per Watt	100lm/W
Power Consumption	6 watts @1050mA
Colour Temperature	2700K, 3000K and 4000K
CRI Warm White (3000K)	90 standard
Beam Angle	15, 25, 38, 60 degrees

\*Specification for pureled only, for retrofit lamp options please see alternative lamps page.

### PHYSICAL PROPERTIES


Materials	Solid Bronze or 316 Stainless Steel Flange, Powdercoated Aluminium Body
Ingress Protection	IP67
Standards	AS/NZS 61046, UL 1838, 2108, CSA C22.2 No. 250.7, 250.0-08, CE

### POWER SUPPLY OPTIONS

DRIVER REQ FOR SERIES WIRED ( CC FORMAT ) \*\* | TRANSFORMER REQ FOR PARALLEL WIRED ( CV FORMAT )\*\*\*

\*\* See pages 3-5,7,9 power supplies

\*\*\* See pages 11-12 power supplies



CATEGORY  
RECESSED & INGROUND

#### LUMINAIRE

LLDMV

#### POWER

- /L/S 1050mA INPUT (CC) SERIES WIRED
- /L/D3 2W, 12VAC INPUT (CV) PARALLEL WIRED
- /L/D7 4W, 12VAC INPUT (CV) PARALLEL WIRED
- /L/D10 6W, 12VAC INPUT (CV) PARALLEL WIRED
- MRT16 12V 5W RETROFIT LAMP

#### BEAM

- 15
- 25
- 38
- 60

#### COLOUR

- 15°
- 25°
- 38°
- 60°

#### ACCESSORIES

- 2 2700K
- 3 3000K
- 4 4000K
- 39 3000K, 90+ CRI

- HCL
- CJK
- FL
- GS05

- HEX CELL LOUVRE
- CABLE JOINT KIT
- FROSTED LENS
- GLARE SHIELD

#### MATERIAL/ FINISH

- SBZ
- SS

- SOLID BRONZE
- STAINLESS STEEL

#### /L/S PURELED SERIES WIRED

Remote constant current driver required.  
Individual fixtures require:  
6VDC@1050mA,  
1050mA maximum

#### /L/D PURELED PARALLEL WIRED

Remote 240VAC-12VAC transformer required. Hunza integrated plug and play driver included.  
Input: 9-15VAC.  
Output: 6VDC @ D3=350mA, D7=700mA, D10=1050mA

PRODUCT CONFIGURATION