


# Down Light Ceiling Mount

DLCM

## DESCRIPTION

The Down Light Ceiling Mount is suitable for surface mounting on ceilings using a 3 bolt internal flange system. This luminaire is water resistant with a 63.5mm diameter mounting base.



PURE LED	
LED Chip	Cree XHP-50-2 Plug and Play, field replaceable LED board, 6Vf
Output	600 lumens @ 1050mA max
Lumens Per Watt	100lm/W
Power Consumption	6 Watts @1050mA
Colour Temperature	2700K, 3000K and 4000K
CRI Warm White (3000K)	90 standard
Beam Angle	15, 25, 38, 60 degrees

PHYSICAL PROPERTIES	
Materials	Powdercoated Aluminium, Solid Copper or 316 Stainless Steel
Ingress Protection	IP66
Standards	AS/NZS 61046, EN60598, UL 1838, CSA 22.2 No. 250.7, CE

POWER SUPPLY OPTIONS	
DRIVER REQ FOR SERIES WIRED ( CC FORMAT ) ** I TRANSFORMER REQ FOR PARALLEL WIRED ( CV FORMAT )*** NO DRIVER REQ FOR GU10	

\*\* See pages 3-5,7,9 power supplies

\*\*\* See pages 11-12 power supplies

CATEGORY  
CEILING MOUNT

LUMINAIRE	POWER	BEAM	COLOUR	ACCESSORIES					MATERIAL/ FINISH	
DLCM										
/L/S	1050mA INPUT (CC) SERIES WIRED	15	15°	2	2700K	HCL	HEX CELL LOUVRE	ALUMINIUM	BK	BLACK
/L/D3	2W, 12VAC INPUT (CV) PARALLEL WIRED	25	25°	3	3000K	SNT	SNOOT		BZ	BRONZE
/L/D7	4W, 12VAC INPUT (CV) PARALLEL WIRED	38	38°	4	4000K	GG	GLARE GUARD		OGR	OLIVE GREEN
/L/D10	6W, 12VAC INPUT (CV) PARALLEL WIRED	60	60°			FL	FROSTED LENS		WH	WHITE
MR16	5W RETROFIT LAMP 12V					FM	FLANGE MOUNT		WB	WHITE BIRCH
GU10	7W SORAA RETROFIT LAMP 230V					CK	CABLE JOINT KIT		DG	DARK GREY
									STAR	SILVER STAR
									CT	CORTEN
									COP	SOLID COPPER
									SS	STAINLESS STEEL

**/L/S PURELED SERIES WIRED**  
Remote constant current driver required.  
Individual fixtures require:  
6VDC@1050mA,  
1050mA maximum

**/L/D PURELED PARALLEL WIRED**  
Remote 240VAC - 12V AC transformer required. Hunza integrated plug and play driver included.  
Input: 9-15VAC.  
Output: 6VDC @ D3=350mA,  
D7=700mA, D10=1050mA

PRODUCT CONFIGURATION