# **Eave Light Eave Light Square**

#### DESCRIPTION

The Eave Light is a recessed downlight, ideal for installation in eaves, soffits, entrance ways, verandahs, carports or covered decks. It can also be used in bathrooms, kitchens or where moisture transfer or decibel rating is a minimum requirement.





| PURE LED               |   |
|------------------------|---|
| LED Chip               | Cree XHP-50-2 Plug and Play, field replaceable LED board, 6Vf |
| Output                 | 600 lumens @ 1050mA max                                       |
| Lumens Per Watt        | 100lm/W   |
| Power Consumption      | 6 Watts @1050mA   |
| Colour Temperature     | 2700K, 3000K and 4000K  |
| CRI Warm White (3000K) | 90 standard   |
| Beam Angle             | 15, 25, 38, 60 degrees  |

<sup>\*</sup>Specification for pureled only, there are no other alternative lamp sources for this fixture.


## PHYSICAL PROPERTIES


| Materials          | Powdercoated Aluminium, Solid Copper or 316 Stainless Steel |
|--------------------|---|
| Ingress Protection | IP66  |
| Standards          | AS/NZS 61046, UL2108 (LED only), CSA C22.2 No. 250.0-08, CE |

### **POWER SUPPLY OPTIONS**

DRIVER REQ FOR SERIES WIRED ( CC FORMAT ) \*\* | TRANSFORMER REQ FOR PARALLEL WIRED ( CV FORMAT ) \*\*\* NO DRIVER REQ FOR RETRO 'R' (INTEGRAL 230V IN)







FROSTED LENS

CABLE JOINT KIT



