

Driveway Light

DWL

DESCRIPTION

The Driveway Light is an adjustable uplighter, designed for mounting flush with the surface of a driveways, hotel floors, building foyers, etc. There is no lip to trip over and can be driven over or walked upon without risk of damage.


PURE LED	
LED Chip	Cree XHP-50-2 Plug and Play, field replaceable LED board, 6Vf
Output	600lumens @ 1050mA max
Lumens Per Watt	100lm/W
Power Consumption	6 watts @1050mA
Colour Temperature	2700K, 3000K and 4000K
CRI Warm White (3000K)	90 standard
Beam Angle	15, 25, 38, 60 degrees

*Specification for pureled only for retrofit lamp options please see alternative page.

PHYSICAL PROPERTIES	
Materials	Solid Bronze or 316 Stainless Steel Flange, Powdercoated Aluminium Body
Ingress Protection	IP67
Standards	AS/NZS 61046, UL 1838, 2108, CSA C22.2 No. 250.7, 250.0-08, CE

POWER SUPPLY OPTIONS	
DRIVER REQ FOR SERIES WIRED (CC FORMAT) ** I TRANSFORMER REQ FOR PARALLEL WIRED (CV FORMAT)***	

** See pages 3-5,7,9 power supplies, *** See pages 11-12 power supplies



CATEGORY
RECESSED & INGROUND

PRODUCT CONFIGURATION

LUMINAIRE	POWER	BEAM	COLOUR	ACCESSORIES					MATERIAL/ FINISH	
DWL										
/L/S	1050mA INPUT (CC) SERIES WIRED	15	15°	2	2700K	HCL	HEX CELL LOUVRE	SBZ	SOLID BRONZE	
/L/D3	2W, 12VAC INPUT (CV) PARALLEL WIRED	25	25°	3	3000K	CJK	CABLE JOINT KIT	SS	STAINLESS STEEL	
/L/D7	4W, 12VAC INPUT (CV) PARALLEL WIRED	38	38°	4	4000K	FL	FROSTED LENS			
/L/D10	6W, 12VAC INPUT (CV) PARALLEL WIRED	60	60°			GS05	GLARE SHIELD			
MR16	12V 5W RETROFIT LAMP									
/L/S PURELED SERIES WIRED		/L/D PURELED PARALLEL WIRED								
Remote constant current driver required.		Remote 240VAC-12VAC transformer required. Hunza integrated plug and play driver included.								
Individual fixtures require:		Input: 9-15VAC.								
6VDC@1050mA,		Output: 6VDC @ D3=350mA,								
1050mA maximum		D7=700mA, D10=1050mA								