

Euro Spot

ES

DESCRIPTION

The Euro Spot is an extra compact luminaire, designed for situations where the fixture needs to be unobtrusive or concealed.

PURE LED	
LED Chip	Cree XHP-50-2 Plug and Play field replaceable LED board, 6Vf
Output	420 Lumens @ 700mA max
Lumens Per Watt	105lm/W
Power Consumption	4.2 watts @ 700mA
Colour Temperature	2700K, 3000K and 4000K
CRI Warm White (3000K)	90 standard
Beam Angle	15, 25, 38, 60 degrees

*Specification for pureled only no retrofit lamp options available for this fixture

PHYSICAL PROPERTIES	
Materials	Solid Copper or 316 Stainless Steel
Ingress Protection	IP66
Standards	AS/NZS 61046, UL 1838, 2108, CSA C22.2 No. 250.7, 250.0-08, CE

POWER SUPPLY OPTIONS	
DRIVER REQ FOR SERIES WIRED (CC FORMAT) ** TRANSFORMER REQ FOR PARALLEL WIRED (CV FORMAT)***	

** See pages 2,6-7,9 power supplies

*** See pages 11-12 power supplies

CATEGORY
GROUND AND DECK



ESS



ES

PRODUCT CONFIGURATION

LUMINAIRE

ES

ESS

POWER

BEAM

COLOUR

ACCESSORIES

MATERIAL/
FINISH

15

25

38

60

15°

25°

38°

60°

2

3

4

39

2700K

3000K

4000K

3000K,90+ CRI

HCL

FL

CJK

HEX CELL LOUVRE

FROSTED LENS

CABLE JOINT KIT

COP

SS

SOLID COPPER

STAINLESS STEEL

/L/S PURELED SERIES WIRED

Remote constant current driver required.

Individual fixtures require:

6VDC@700mA,

700mA maximum

/L/D PURELED PARALLEL WIRED

Remote 240VAC-12VAC transformer required.

Hunza integrated plug and play driver included.

Input: 9-15VAC.

Output: 6VDC @ D3=350mA,

D7=700mA