

Hanging Light

HL

DESCRIPTION

The Hanging Light is a single spotlight which can be easily hung from high vantage points, including trees, fences and over-hangs, providing a dynamic moon lighting effect. The luminaire comes standard with a 3 metre cable and Stainless Steel wire.



PURE LED	
LED Chip	Cree XHP-50-2 Plug and Play, field replaceable LED board, 6Vf
Output	600lumens @ 1050mA max
Lumens Per Watt	100lm/W
Power Consumption	6 watts @1050mA
Colour Temperature	2700K, 3000K and 4000K
CRI Warm White (3000K)	90 standard
Beam Angle	15, 25, 38, 60 degrees


*Specification for pureled only for retrofit lamp options please see alternative lamps page.

PHYSICAL PROPERTIES	
Materials	Powdercoated Aluminium, Solid Copper or 316 Stainless Steel
Ingress Protection	IP66
Standards	AS/NZS 61046, UL 1838, 2108, CSA C22.2 No. 250.7, 250.0-08, CE

POWER SUPPLY OPTIONS	
DRIVER REQ FOR SERIES WIRED (CC FORMAT) ** TRANSFORMER REQ FOR PARALLEL WIRED (CV FORMAT)***	

** See pages 3-5,7,9 power supplies

*** See pages 11-12 power supplies



CATEGORY
TREE MOUNT

LUMINAIRE	POWER	BEAM	COLOUR		ACCESSORIES					MATERIAL/ FINISH	
HL											
/L/S	1050mA INPUT (CC) SERIES WIRED	15	15°	2	2700K	HCL	HEX CELL LOUVRE	BK	BLACK		
/L/D3	2W, 12VAC INPUT (CV) PARALLEL WIRED	25	25°	3	3000K	SNT	SNOOT	BZ	BRONZE		
/L/D7	4W, 12VAC INPUT (CV) PARALLEL WIRED	38	38°	4	4000K	GG	GLARE GUARD	OGR	OLIVE GREEN		
/L/D10	6W, 12VAC INPUT (CV) PARALLEL WIRED	60	60°			FL	FROSTED LENS	WH	WHITE		
MR16	5W RETROFIT LAMP 12V					CJK	CABLE JOINT KIT	WB	WHITE BIRCH		
						CAT	CATENARY MOUNT	DG	DARK GREY		
								STAR	SILVER STAR		
								CT	CORTEN		
								COP	SOLID COPPER		
								SS	STAINLESS STEEL		

/L/S PURELED SERIES WIRED, Remote constant current driver required.
Individual fixtures require:
6VDC@1050mA,
1050mA maximum

/L/D PURELED PARALLEL WIRED, Remote 240VAC - 12V AC transformer required.
Hunza integrated plug and play driver included.
Input: 9-15VAC.
Output: 6VDC @ D3=350mA,
D7=700mA, D10=1050mA

PRODUCT CONFIGURATION