DESCRIPTION

The Twin Bar Light is ideal for wall or sign illumination. The luminaire has two individual spot lights which can be aimed in two entirely different directions. Each head has a fully adjustable arm allowing 360 degree rotation and 0 - 90 degree elevation adjustment.

PURE LED	
LED Chip	Cree XHP-50-2 Plug and Play, field replaceable LED board, 2x6Vf
Output	2x600 lumens @ 1050mA
Lumens Per Watt	100lm/W
Power Consumption	12watts @ 1050mA
Colour Temperature	2700K, 3000K and 4000K
CRI Warm White (3000K)	90 standard
Beam Angle	15, 25, 38, 60 degrees

^{*}Specification for pureled only for retrofit lamp options please see alternative lamp page.


PHYSICAL PROPERTIES

Materials	Powdercoated Aluminium, Solid Copper or 316 Stainless Steel
Ingress Protection	IP66
Standards	AS/NZS 61046, UL 1838, CSA C22.2 No. 250.7

POWER SUPPLY OPTIONS

DRIVER REQ FOR SERIES WIRED (CC FORMAT) ** | TRANSFORMER REQ FOR PARALLEL WIRED (CV FORMAT)***





MATERIAL/ LUMINAIRE **BEAM** COLOUR **ACCESSORIES FINISH POWER** TBL HCL HEX CELL LOUVRE BLACK 2700K 15° 2 BK 1L/S 1050mA INPUT (CC) SERIES WIRED SNT SNOOT 25 25° 3 3000K BZ **BRONZE** /L/D3 2x2W, 12VAC INPUT (CV) PARALLEL WIRED GLARE GUARD 4 4000K GG OGR OLIVE GREEN 38 389 2x4W, 12VAC INPUT (CV) PARALLEL WIRED 1/D7 3000K,90+ CRI LF FROSTED LENS WH WHITE 39 609 /L/D10 2x6W, 12VAC INPUT (CV) PARALLEL WIRED CJK CABLE JOINT KIT WHITE BIRCH WB MR16 5W RETROFIT LAMP 12V DG DARK GREY STAR SILVER STAR CORTEN CT /L/S PURELED SERIES WIRED /L/D PURELED PARALLEL WIRED Remote constant current driver required. Remote 240VAC - 12V AC transformer required. COP SOLID COPPER Individual fixtures require: 2x Hunza integrated plug and play driver included. STAINLESS STEEL 2x6VDC@1050mA, Input: 9-15VAC. 1050mA maximum Output: 6VDC @ D3=350mA, D7=700mA, D10=1050mA

See pages 3-5,7,9 power supplies

^{***} See pages 11-12 power supplies