

# Spike Spot Adjustable

SS/A

## DESCRIPTION

The Spike Spot Adjustable has been designed for easy installation into the earth and is ideal for illuminating a bush, tree or any landscape feature. The fully adjustable head allows 360 degree rotation and 0-90 degree elevation.

| PURE LED               |   |
|------------------------|---|
| LED Chip               | Cree XHP-50-2 Plug and Play, field replaceable LED board, 6Vf |
| Output                 | 600 lumens @ 1050mA   |
| Lumens Per Watt        | 100lm/W   |
| Power Consumption      | 6watts @ 1050mA   |
| Colour Temperature     | 2700K, 3000K and 4000K  |
| CRI Warm White (3000K) | 90 standard   |
| Beam Angle             | 15, 25, 38, 60 degrees  |

\*Specification for pureled only for retrofit lamp options please see alternative lamp page.

## PHYSICAL PROPERTIES

|                    |   |
|--------------------|---|
| Materials          | Powdercoated Aluminium, Solid Copper or 316 Stainless Steel |
| Ingress Protection | IP66  |
| Standards          | AS/NZS 61046, UL 1838, CSA C22.2 No. 250.7                  |

## POWER SUPPLY OPTIONS

DRIVER REQ FOR SERIES WIRED ( CC FORMAT ) \*\* I TRANSFORMER REQ FOR PARALLEL WIRED ( CV FORMAT )\*\*\*

\*\* See pages 3-5,7,9 power supplies

\*\*\* See pages 11-12 power supplies



CATEGORY  
GROUND AND DECK

PRODUCT CONFIGURATION

LUMINAIRE

SS/A

/L/S

/D3

/D7

/D10

MR16

POWER

1050mA INPUT (CC) SERIES WIRED

2W, 12VAC INPUT (CV) PARALLEL WIRED

4W, 12VAC INPUT (CV) PARALLEL WIRED

6W, 12VAC INPUT (CV) PARALLEL WIRED

5W RETROFIT LAMP 12V

BEAM

15

25

38

60

COLOUR

15°

25°

38°

60°

ACCESSORIES

2

3

4

39

2700K

3000K

4000K

3000K, 90+ CRI

HCL

SNT

GG

LF

LKN

CLK

HEX CELL LOUVRE

SNOOT

GLARE GUARD

FROSTED LENS

LOCKING KNUCKLE

CABLE JOINT KIT

MATERIAL/ FINISH

BK

BZ

OGR

WH

WB

DG

STAR

CT

COP

SS

BLACK

BRONZE

OLIVE GREEN

WHITE

WHITE BIRCH

DARK GREY

SILVER STAR

CORTEN

SOLID COPPER

STAINLESS STEEL

/L/S PURELED SERIES WIRED

Remote constant current driver required.

Individual fixtures require:

6VDC@1050mA,

1050mA maximum

/L/D PURELED PARALLEL WIRED

Remote 240VAC - 12V AC transformer required.

Hunza integrated plug and play driver included.

Input: 9-15VAC.

Output: 6VDC @ D3=350mA,

D7=700mA, D10=1050mA