


# Mini Bollard

BOLMINI

## DESCRIPTION

The Mini Bollard is an unobtrusive, low profile luminaire, that provides soft lighting effects on decks, railings and posts. The acrylic lens reflects light at two angles through an anti-glare mesh, directly onto the ground and horizontally to illuminate the surrounding landscape. It is not suited for ground installation.



## PURE LED

LED Chip	Cree XPG-3 Plug and Play, field replaceable PCB board, 3Vf
Output	120 Lumens @ 700mA max
Lumens Per Watt	60 lm/W
Power Consumption	2 watts@ 700mA
Colour Temperature	2700K, 3000K and 4000K
CRI Warm White (3000K)	90 standard
Beam Angle	360 degrees

\*Specification for pureled only no retrofit lamp options available for this fixture

## PHYSICAL PROPERTIES

Materials	Powdercoated Aluminium, Solid Copper or 316 Stainless Steel
Ingress Protection	IP66+
Standards	AS/NZS 61046, UL 1838, 2108, CSA C22.2 No. 250.7, 250.0-08, CE

## POWER SUPPLY OPTIONS

DRIVER REQ FOR SERIES WIRED ( CC FORMAT ) \*\*

\*\* See pages 2,6-7,9 power supplies

CATEGORY  
GROUND AND DECK

### LUMINAIRE

BOLMINI

### POWER

/L/S 700mA INPUT (CC) SERIES WIRED

### BEAM

360

### COLOUR

360°

### ACCESSORIES

2

3

4

2700K

3000K

4000K

FM90

CJK

BOLOP

HOOD140

FLANGE MOUNT 90

CABLE JOINT KIT

OPAQUE LENS

HOOD 140MM

### MATERIAL/ FINISH

BK  
BZ  
OGR  
WH  
WB  
DG  
STAR  
CT

COP  
SS

BLACK  
BRONZE  
OLIVE GREEN  
WHITE  
WHITE BIRCH  
DARK GREY  
SILVER STAR  
CORTEN

SOLID COPPER  
STAINLESS STEEL

**/L/S PURELED SERIES WIRED**  
Remote constant current driver required.  
Individual fixtures require:  
3VDC@700mA,  
700mA maximum

PRODUCT CONFIGURATION