

Path Light

PL

DESCRIPTION

The Path Light is ideal for lighting flat areas, decks, paved courtyards or edge lighting paths. It has a low profile and directs light horizontally through a custom made TIR Borosilica glass lens. This lens has been developed to prevent dirt, mud, grass clippings or water from entering the optics area, keeping with its IP67 rating.

CATEGORY
RECESSED & INGROUND



PURE LED

LED Chip	Cree XHP-50-2 Plug and Play, field replaceable LED board, 6Vf
Output	300 lumens @ 1050mA max
Lumens Per Watt	50lm/W
Power Consumption	6 Watts @1050mA
Colour Temperature	2700K, 3000K and 4000K
CRI Warm White (3000K)	90 standard
Beam Angle	90, 90 x 90, 180, 270, 360 degrees

*Specification for pureled only, for retrofit lamp options please see alternative lamps page.

PHYSICAL PROPERTIES

Materials	Solid powdercoated Aluminium, Solid Copper or 316 Stainless Steel
Ingress Protection	IP67
Standards	AS/NZS 61046, UL 1838, 2108, CSA C22.2 No. 250.7, 250.0-08, CE

POWER SUPPLY OPTIONS

DRIVER REQ FOR SERIES WIRED (CC FORMAT) ** | TRANSFORMER REQ FOR PARALLEL WIRED (CV FORMAT)***

** See pages 3-5,7,9 power supplies

*** See pages 11-12 power supplies

