

## NOTES:

- 1. FIRST SUFFIX "X" INDICATES SPRING PRESSURE
- 2. SECOND AND THIRD SUFFIX "XX" INDICATES MATERIAL AND COLOR: 01- CLEAR GAMMA GRADE PVC 21- CLEAR GAMMA GRADE POLYCARBONATE.
- 3. CRITICAL DIMENSIONS ARE CIRCLED, AND SUBJECT TO INSPECTION.
- 4. DIMENSIONS IN PARENTHESES ARE FOR REFERENCE ONLY.
- 5. ALL DIMENSIONS ARE IN INCHES WITH NOMINAL, DIMENSIONS IN MILLIMETERS BELOW.
- 6. LUER COMPATIBLE WITH ISO 594-2.

FIRST SUFFIX	SECOND SUFFIX "XX"	SPRING PRESSURE	CHECK VALVE & BODY MATERIAL
0	21	6 PSI	CLEAR POLYCARBONATE
2	01	15 PSI	CLEAR PVC
5	21	30 PSI	CLEAR POLYCARBONATE
6	21	2.5 PSI	CLEAR POLYCARBONATE
7	21	22 PSI	CLEAR POLYCARBONATE

QUALITY CRITERIA:

O.D. FLASH 0.015 MAX. (0.4mm)

GATE VESTIGE 0.01 MAX. (0.3mm)

EMBEDDED PARTICLES, BUBBLES, SPOTS, STAINS: 0.3mm<sup>2</sup> MAX. NO MORE THAN 3 PER PART.

	DRAWN BY	DMCDM		<sup>PATE</sup> 6/29/03	<b></b>	J 11-11 D-	1
	APPROVED BY		C	Type in Cus	ob Pr	Nalkey-Ro	perts
	MATERIAL				TITLE	CHECK VALVE W/ NO	771 F &
MOLDED PARTS: GATES, PARTING LINES, AND FLASH PER QUALITY CRITERIA	FINISH					THR'D ADAPTER	
PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS SOLE PROPERTY	UNLESS OTHERWISE : DIMENSIONS ARE IN IN TOLERANCES:		THIRD ANGL	E PROJECTION	B	C246203XXX	F REV
OF HALKEY-ROBERTS CORPORATION ST. PETERSBURG, FL. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF HALKEY-ROBERTS CORPORATION IS PROHIBITED.	ANGULAR: ± 1° TWO PLACE DECIMAL THREE PLACE DECIMAL		•		SCALE 4:1	DO NOT SCALE DRAWING	1 OF 2