

KI-6BW3

6MP IP True WDR Mini Bullet

Features


- 6MP Resolution
- True WDR
- H.265/H.265+
- IP67
- IR up to 100ft
- 2.8mm Fixed Lens
- Micro SD Card Slot
- 12VDC, PoE
- $\Phi 2.8'' \times 6.1''$



Specification

Image Sensor	1/2.9" progressive scan CMOS
Min. Illumination	0.01 Lux @ (F1.2, AGC ON), 0 Lux with IR
Shutter time	1/3s ~ 1/100,000s
Lens	2.8mm @ F2.0
Day & night	IR cut filter with auto switch
Digital noise reduction	3D DNR
Wide dynamic range	True WDR 120dB
Video compression	H.265 / H.265+ / H.264+ / H.264 / MJPEG
Max. image resolution	3072 x 2048
Frame rate	20fps (3072x2048), 20fps(2560x1440)
Image settings	Saturation, brightness, contrast, sharpness adjustable through client software or web browser
Network storage	Support microSD/SDHC/SDXC card (128Gb) local storage, NAS (NFS,SMB/CIFS), ANR
Alarm trigger	Motion detection, tampering alarm, network disconnect, IP address conflict, storage exception
Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, SNMP, HTTPS, FTP, 802.1x, Qos
Security	User Authentication, reset button, flickerless, dual stream, heartbeat, mirror, watermark
Communication interface	1 RJ45 10M/ 100 M Ethernet interface
Operating conditions	-30 °C ~ 60 °C (-22 °F ~ 140 °F) humidity 95% or less (non-condensing)
Power supply	12 VDC +/- 25%, PoE (802.3af)
Power consumption	Max 6W, PoE(802.3af, class 3), 7W
Weather proof rating	IP67
IR range	UP to 100ft
Dimension	$\Phi 2.8'' \times 6.1''$
Weight	0.9lbs
Electrical Box	KI-AE280-XS

Dimension



Mount Option



Electrical Box
KI-AE280-XS