



SABER® M700™ ERT

EXTENDED RANGE TACTICAL RIFLE

SNIPER'S HIDE SPECIAL EDITION

Modular by Definition... Performance Engineered by Design

SABER® M700™ ERT

Snipers-Hide-Rifle.com

EXTENDED RANGE TACTICAL RIFLE

The Sniper’s Hide Special Edition SABER® M700™ ERT is the operational standard for a full featured “Cross-Over” precision rifle for recreational long range shooting and multi-sport long gun competition. Developed in close collaboration with Frank Galli, former US Marine Corps Scout Sniper and founder of SnipersHide.com, the SABER M700 ERT is a custom rifle platform designed to provide entry level users with an accurate, ergonomically adjustable “range-ready” rifle designed for the tactical shooting sports. Chambered in popular .308 Win and 6.5 Creedmoor calibers, the SABER M700 ERT provides precision long range rifle shooters with consistent sub-MOA precision to distances greater than 1,000 yards.

Designed for accurate and dependable long range precision shooting, the SABER® M700™ ERT provides users with many noteworthy operational features. Each rifle uses a hand select Model 700 SPS/AAC-SD barreled action that is inspected, gauged, hand-worked and accurized by APO’s experienced Precision Weapons Section. **The Action:** Remington’s proven Model 700 bolt action receiver is manufactured from quality carbon steel. **The Barrel:** Hammer forged carbon steel - medium-heavy contour - threaded muzzle, and highly efficient muzzle brake. **The Trigger:** Trigger Tech adjustable single-stage trigger set to break cleanly and crisply at 3 lbs.

The Patented SABER Chassis: Enhanced SABER MRCS-AR modular, lightweight and ergonomically adjustable. SABER rifle chassis are rugged, reconfigurable, low maintenance, and require no bedding to deliver optimal accuracy. Manufactured from aerospace grade aluminum alloys and carbon reinforced polymers the MRCS-AR is impervious to foul weather conditions, and hot/cold temperature extremes. **The Ergonomic Shoulder Stock:** Ergonomically adjustable TASS Tactically Adjustable Shoulder Stock, provides screw-in length of pull spacers, push button vertical recoil pad drop positioning and thumbscrew cheek piece height adjustment - all positive locking. The TASS shoulder stock utilizes a Butt Hook for non-shooting hand support, and an optional rapidly adjustable 3-position field monopod is available as a user installable option. The shoulder stock is mounted to the SABER chassis with a strong double locking folding hinge.

The SABER® M700™ ERT has a user adjustable hand grip to customize the distance-to-trigger for large and small hands and an interchangeable near vertical 11° grip angle. The SABER® M700™ ERT is fitted with an ambidextrous paddle lever magazine catch-release & comes with one five-round polymer magazine.

The SABER® M700™ ERT aluminum alloy forend has a unique octagonal design with Sniper’s Hide inspired, integrated mirage band and M-LOK® accessory rail mounting locations at 3, 6, and 9 o’clock positions. At 6 o’clock, both an M-LOK Picatinny rail segment and bipod stud are standard.

Ergonomic adjustability, modularity, shoot-ability, and low-felt recoil with Sub-MOA precision are all hallmarks of the Sniper’s Hide Special Edition SABER® M700™ ERT Rifle.



Utility & Design Patents at
APO-Patents.com

Shown with Optional Accessories



Order Your Custom Rifle at
Snipers-Hide-Rifle.com Today!



Trusted to Make it Better!

CALIBER

.308 Winchester - 6.5 Creedmoor

ACTION

Remington Model 700 Short Action, Hand Selected, Gauged & Accurized

BOLT

Factory Two-Lug Bolt Design

(optional one piece bolt with Mini-16 Extractor and Tactical Bolt Knob)

TRIGGER

Trigger Tech Adjustable Single-Stage (set to 3 lbs. \pm 1/2 lb.)

BARREL

- .20" .308 Win Medium Heavy Contour – 1:10" Twist
5/8-24 Threaded Muzzle
- 22" .6.5 Creedmoor Medium Heavy Contour – 1:8" Twist
5/8-24 Threaded Muzzle

MUZZLE BRAKE

Arclight SC-3

RIFLE CHASSIS - MODULAR

SABER RSA-A3 MRCS-AR Enhanced

SHOULDER STOCK - ERGONOMIC/ADJUSTABLE

TASS - Tactically Adjustable Shoulder Stock, Positive Locking

- Limbsaver Premium Recoil Pad
- Butt Hook, Interchangeable
- Flush Cup Sling Swivel Sockets x2
- Monopod, 3-Position (optional)

STOCK INTERFACE

Double Locking Alloy Folding Hinge, Tension Adjustable

(optional Fixed and Stainless Steel Lockable Hinge)

MAGAZINE - DETACHABLE BOX

- 5rd Magpul PMAG Polymer Box Magazine x1
- 10rd Magpul PMAG Polymer Box Magazine (optional)

HAND GRIP

MOE Hand Grip (Changeable AR-15/M-16 Style)

GRIP ANGLE ADAPTERS

11° (optional 17.5° and 27°)

FOREND

- AR-08 Octagonal Aluminum Alloy M-LOK® Accessory Mounting
Locations at 3-6-9 o’clock Positions
- Flush Cup Sling Swivel Socket (optional)

MONOLITHIC PICATINNY SCOPE RAIL

20 MOA Slant, MIL-STD 1913, Co-Linear Mounted Day and Night Optics (optional)

ACCESSORY RAILS

- M-LOK Picatinny Accessory Rails (optional)
- M-LOK Accessories Kit (optional)

SURFACE COATINGS

Black Oxide and Cerakote Coating

COLORS

- Barreled Action – Black
- Chassis – Cerakote Armor Black, Flat Dark Earth, OD Green,
or Sniper Grey

ACCURACY

Sub-MOA Match-Grade Ammunition

PACKAGING

- Heavy Duty Corrugated Shipping Container
- Hard Lockable Transit Case with Custom Foam Interior (optional)
- Nylon Padded Field Carry Bag (optional)

BASE RIFLE WEIGHT & DIMENSIONS (approx)

- .308Win - 20" Barrel | 11.25 lbs | Length 41" | Folded Length 31.5"
- 6.5CM - 22" Barrel | 11.50 lbs | Length 43" | Folded Length 33.5"

Specifications are Subject to Change. Custom Configurations Available.

SABER® M700™ ERT

Snipers-Hide-Rifle.com

EXTENDED RANGE TACTICAL RIFLE

.308 WINCHESTER EXTERNAL BALLISTICS

175gr OTM 2600fps .547BC

Distance		Elevation	Elevation	Velocity
Yards	Meters	MOA	MILS	FPS
100	91	0	0	2434
200	183	1.25	0.4	2274
300	271	3.75	1.1	2120
400	366	7.00	2.0	1970
500	457	10.50	3.1	1826
600	549	14.50	4.2	1688
700	640	19.25	5.6	1555
800	732	24.25	7.1	1428
900	823	30.00	8.8	1307
1000	914	36.75	10.7	1197
1100	1006	44.25	12.8	1107

Station Pressure: 29.53 in. Hg.	Caliber: .308 Winchester	Bullet Weight: 175gr
Humidity: 78%	Bullet Type: BTHP Open Tip Match	Ballistic Coefficient: 0.547 (G1)
Temperature: 59°	Velocity: 2600± Feet Per Second	Rifle: SABER M700 ERT
Elevation: 0ft ASL		.308Win 20" BBL

Standard Metro Atmospheric Conditions

6.5 CREEDMOOR EXTERNAL BALLISTICS

130gr Hybrid OTM 2875fps .560BC

Distance		Elevation	Elevation	Velocity
Yards	Meters	MOA	MILS	FPS
100	91	0	0	2704
200	183	0.75	0.2	2537
300	271	2.75	0.8	2377
400	366	5.25	1.5	2221
500	457	8.00	2.3	2071
600	549	11.25	3.2	1926
700	640	14.75	4.3	1786
800	732	18.75	5.4	1651
900	823	23.00	6.7	1522
1000	914	28.00	8.2	1398
1100	1006	33.75	9.8	1282

Station Pressure: 29.53 in. Hg.	Caliber: 6.5 Creedmoor	Bullet Weight: 130gr
Humidity: 78%	Bullet Type: VLD OTM	Ballistic Coefficient: 0.560
Temperature: 59°	Velocity: 2975± Feet Per Second	Rifle: SABER M700 ERT
Elevation: 0ft ASL		6.5 Creedmoor 22"

Standard Metro Atmospheric Conditions



Made in USA

APO
ASHBURY PRECISION ORDNANCE
The Precision Long Range Rifle Specialists

Ashbury Precision Ordnance Mfg. • 84 Business Park Circle • Ruckersville • Virginia • 22968 • 434-296-8600
AshburyPrecisionOrdnance.com • info@AshburyPrecisionOrdnance.com

M700 is a trademark and used with the authorization of RA Brands, L.L.C.

